N100 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM

(Full Frame Format Lens)

Columns: CAMERA LENS → GEAR → PORT ADAPTOR → EXTENSION RING → PORT → MOUNT CONVERTER → WET LENS → OPTICAL PERFORMANCE

MACRO (FULL FRAME)

Sony SEL50M18 FE 50mm f/1.8
- **37123** N100 Macro Port 55
- **37123** N100 Macro Port 55
  - * These setups are only recommanded to use with Crop/APS-C format enabled to avoid vignetting
  - SMC/CMC Option 1 - M67 Thread: **81228** M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging) → **81301** CMC - 1 — Max. Magnification 0.9X; Working Distance 60-77mm
  - SMC/CMC Option 2 - Bayonet Mount: **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC → **81302** CMC - 2 — Max. Magnification 0.6X; Working Distance 37-48mm
  - **83250** M67 to Bayonet Mount Converter II (included in all MWL-1 packaging) → **86201** MWL - 1 — Lens FOV 31°; Converted FOV 116°

Sony SEL50M28 FE 50mm f/2.8 Macro
- **37402** N100 Extension Ring 40 → **37127** N100 Flat Port 32

Sony SEL55F18Z AE Sonnar T* FE 55mm F1.8 ZA
- **37123** N100 Macro Port 55

Sony SEL90M28G FE 90mm f/2.8 Macro G OSS
- **37147** SE90-F → **37126** N100 Macro Port 105
  - SMC/CMC Option 1 - M67 Thread: **81228** M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging) → **81201** SMC - 1 — Max. Magnification 2.2X; Working Distance 45-93mm
  - SMC/CMC Option 2 - Bayonet Mount: **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC → **81202** SMC - 2 — Max. Magnification 3.4X; Working Distance 22-36mm
  - **83250** M67 to Bayonet Mount Converter II → **87303** EMWL Set#3 — Lens FOV 27°; Converted FOV 60°/100°/130°/160°

Sigma 105mm F2.8 DG DN Macro Art
- **37166** SGE105-F
  - **37125** N100 Macro Port 110
    - SMC/CMC Option 1 - M67 Thread: **81228** M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging) → **81201** SMC - 1 — Max. Magnification 2.3X; Working Distance 49-80mm
    - SMC/CMC Option 2 - Bayonet Mount: **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC → **81202** SMC - 2 — Max. Magnification 3.6X; Working Distance 26-35mm
  - **37305** N100 to N120 35.5mm Port Adaptor II → **22120** N120 Extension Ring 20 II → **18701** Macro Port 60

Laowa 24mm f/14 2X Macro Probe
- **19155** N120 DSLR Gear Set → **37305** N100 to N120 35.5mm Port Adaptor II → **22170 + 22171** N120 Extension Ring 70 II + Focus Knob → **16336** N120 Port Adaptor

STANDARD ZOOM (FULL FRAME)

Sony FE 20-70mm f/4 G
- **37174** SFE2070-Z → **37305** N100 to N120 35.5mm Port Adaptor II
  - * **85204** N120 WACP - 2 (* slight vignetting at 20mm in RAW format) — Lens FOV 94-59°; Converted FOV 116-73°; Zoom Range 20-38mm
  - **22120** N120 Extension Ring 20 II → **85206** N120/N100 WACP - 1B; **85201** N120 WACP - 1 — Lens FOV 75-71°; Converted FOV 130-123°; Zoom Range 28-30mm
  - **22135** N120 Extension Ring 35 II → **18809** 180mm Optical Glass Wide Angle Port
  - **22140** N120 Extension Ring 40 II → **18802** 8.5" Acrylic dome port; **18812** 230mm Optical Glass Wide Angle Port; * **18815** 250mm Optical Glass Wide Angle Port

Sony SEL2470Z Vario-Tessar T* FE 24-70mm F4 ZA OSS
- **37149** SE2470-Z / **37149 + 37148** SE2470-Z + SE2470-F → **37305** N100 to N120 35.5mm Port Adaptor II
  - **85204** N120 WACP - 2 — Lens FOV 84-34°; Converted FOV 98-72°; Zoom Range 24-35mm
  - **22130** N120 Extension Ring 30 II → **18809** 180mm Optical Glass Wide Angle Port

Sony SEL2470GM FE 24-70mm f/2.8 GM
- **37151** SFE2470GM-Z / **37151 + 37152** SFE2470GM-Z + SFE2470GM-F → **37305** N100 to N120 35.5mm Port Adaptor II
  - **22130** N120 Extension Ring 30 II → **85204** N120 WACP - 2 — Lens FOV 84-34°; Converted FOV 98-72°; Zoom Range 24-35mm
  - **22160** N120 Extension Ring 60 II → **18809** 180mm Optical Glass Wide Angle Port

Sony SEL2470GM2 FE 24-70mm f/2.8 GM II
- **37173** SFE2470II-Z → **37305** N100 to N120 35.5mm Port Adaptor II
  - **22150** N120 Extension Ring 50 II → **18802** 8.5" Acrylic dome port; **18812** 230mm Optical Glass Wide Angle Port; * **18815** 250mm Optical Glass Wide Angle Port
  - **22155** N120 Extension Ring 55 II → **18809** 180mm Optical Glass Wide Angle Port

Sony SEL28F20 FE 28mm f/2
- **37150** SE28-F
  - **37127** N100 Flat Port 32 → **83250** M67 to Bayonet Mount Converter II → **83202** WWL - 1B
  - **37401** N100 Extension Ring 30 → **85205** N100 WACP - C; * **85206** N120/N100 WACP - 1B; **85203** N100 WACP - 1
  - Lens FOV 75°; Converted FOV 130°

Sony SEL2860 FE 28-60mm F4-5.6
- **37163** SFE2860-Z
  - **37401 + 37401** N100 Extension Ring 30 + N100 Extension Ring 30 → **37129** N100 180mm Optical Glass Wide Angle Port
  - **37401** N100 Extension Ring 30 → * **85206** N120/N100 WACP - 1B; **85203** N100 WACP - 1; **85205** N100 WACP - C — Lens FOV 75-40°; Converted FOV 130-69°
  - **37408** N100 Extension Ring 35 → **85207** N120/N100 FCP - 1 (* slight vignetting at 28mm) — Lens FOV 75-40°; Converted FOV 170-74°
  - **37305** N100 to N120 35.5mm Port Adaptor II
    - **22130** N120 Extension Ring 30 II → * **18809** 180mm Optical Glass Wide Angle Port
    - **85207** N120/N100 FCP - 1 (* slight vignetting at 28mm) — Lens FOV 75-40°; Converted FOV 170-74°
- **37163 + 37168** SFE2860-Z + SFE2860-F (WACP-1) → **37305** N100 to N120 35.5mm Port Adaptor II → **85206** N120/N100 WACP - 1B; **85201** N120 WACP - 1 — Lens FOV 75-39°; Converted FOV 130-68°
- **37163 + 37164** SFE2860-Z + SFE2860-F → **37165** N100 Flat Port 45 with Focus Knob
  - **83250** M67 to Bayonet Mount Converter II → **83202** WWL - 1B — Lens FOV 75-40°; Converted FOV 130-69°
  - SMC/CMC Option 1 - M67 Thread: **81228** M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging) → **81301** CMC - 1 — Max. Magnification 0.9X; Working Distance 55-80mm
  - SMC/CMC Option 2 - Bayonet Mount: **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC → **81302** CMC - 2 — Max. Magnification 0.7X; Working Distance 83-135mm

Sony SEL2870 FE 28-70mm F3.5-5.6 OSS
- **37141** SE2870-Z
  - **37403** N100 Extension Ring 50 → * **85206** N120/N100 WACP - 1B; **85203** N100 WACP - 1; **85205** N100 WACP - C — Lens FOV 75-34°; Converted FOV 130-59°
  - **37401 + 37401** N100 Extension Ring 30 II + N100 Extension Ring 30 II → **85207** N120/N100 FCP - 1 — Lens FOV 75-34°; Converted FOV 170-62°
  - **37124** Flat port 66 with M77 Thread → **83251** M77 to Bayonet Mount Converter II → **86201** MWL - 1 — Lens FOV 39-34°; Converted FOV 150-110°; Zoom Range 60-70mm
- **37141 + 37167** SE2870-Z + SE2870-F → **37305** N100 to N120 35.5mm Port Adaptor II
  - **22120** N120 Extension Ring 20 II → **85206** N120/N100 WACP - 1B; **85201** N120 WACP - 1 — Lens FOV 75-34°; Converted FOV 130-59°
  - **22125** N120 Extension Ring 25 II → **85207** N120/N100 FCP - 1 — Lens FOV 75-34°; Converted FOV 170-62°

Sony SEL35F28Z Sonnar T* FE 35mm F2.8 ZA
- **37122** 4" Wide angle port
- **37130** N100 Flat port 23 → **83250** M67 to Bayonet Mount Converter II → * **83202** WWL - 1B — Lens FOV 62°; Converted FOV 109°

Sigma 24-70mm f/2.8 DG DN Art
- **37171** SSF2470-Z → **37305** N100 to N120 35.5mm Port Adaptor II
  - **22155** N120 Extension Ring 55 II → **18802** 8.5" Acrylic dome port; **18809** 180mm Optical Glass Wide Angle Port; * **18812** 230mm Optical Glass Wide Angle Port
  - **22120** N120 Extension Ring 20 II → * **85204** N120 WACP - 2 — Lens FOV 84-64°; Converted FOV 98-74°; Zoom Range 24-34mm

Tamron 28-75mm f/2.8 Di III RXD
- **37159** STE2875-Z / **37159 + 37160** STE2875-Z + STE2875-F → **37305** N100 to N120 35.5mm Port Adaptor II
  - **22135** N120 Extension Ring 35 II → * **85206** N120/N100 WACP - 1B; **85201** N120 WACP - 1 — Lens FOV 75-52°; Converted FOV 130-90°; Zoom Range 28-45mm
  - **22150** N120 Extension Ring 50 II → **18802** 8.5" Acrylic dome port; **18809** 180mm Optical Glass Wide Angle Port; * **18812** 230mm Optical Glass Wide Angle Port

WIDE ANGLE (FULL FRAME)

Sony SEL1224GM FE 12-24mm F2.8 GM
- **37161** SFE1224GM-Z / **37161 + 37162** SFE1224GM-Z + SFE1224GM-F → **37305** N100 to N120 35.5mm Port Adaptor II → **22155** N120 Extension Ring 55 II → **18812** 230mm Optical Glass Wide Angle Port
  - * This setup is not compatible with Extension Rings I before SN:A055053 09/2016

Sony SEL1224G FE 12-24mm F4 G
- **37153** SFE1224-Z / **37153 + 37154** SFE1224-Z + SFE1224-F → **37305** N100 to N120 35.5mm Port Adaptor II → **22140** N120 Extension Ring 40 II → **18812** 230mm Optical Glass Wide Angle Port

Sony FE 14mm f/1.8 GM
- **37401 + 37402** N100 Extension Ring 30 + N100 Extension Ring 40 → **85207** N120/N100 FCP - 1 — Circular Fisheye (remove shade); Converted FOV 180°; Zoom Range at 14mm only
- **37305** N100 to N120 35.5mm Port Adaptor II
  - **22120** N120 Extension Ring 20 II → **18809** 180mm Optical Glass Wide Angle Port
  - **22130** N120 Extension Ring 30 II → **18802** 8.5" Acrylic dome port; * **18812** 230mm Optical Glass Wide Angle Port; **18815** 250mm Optical Glass Wide Angle Port
  - **22135** N120 Extension Ring 35 II → **85207** N120/N100 FCP - 1 — Circular Fisheye (remove shade); Converted FOV 180°; Zoom Range at 14mm only
- **37306** N100 to N120 25mm Port Adaptor → * **85204** N120 WACP - 2 — Lens FOV 114°; Converted FOV 140°

Sony SEL1635GM FE 16-35mm F2.8 GM
- **37155** SFE1635GM-Z / **37155 + 37156** SFE1635GM-Z + SFE1635GM-F → **37305** N100 to N120 35.5mm Port Adaptor II
  - **22130** N120 Extension Ring 30 II → **85204** N120 WACP - 2 — Lens FOV 107-63°; Converted FOV 128-77°
  - **22160** N120 Extension Ring 60 II → **18809** 180mm Optical Glass Wide Angle Port
  - **22170** N120 Extension Ring 70 II → * **18812** 230mm Optical Glass Wide Angle Port

Sony SEL1635GM2 FE 16-35mm f/2.8 GM II
- **37175** SFE1635GMII-Z → **37305** N100 to N120 35.5mm Port Adaptor II
  - **21110** N120 Extension Ring 10 → **85204** N120 WACP - 2 (* This setup is only compatible with WACP-2 before SN:A526311)
  - **22110** N120 Extension Ring 10 II → * **85204** N120 WACP - 2 (* This setup is only compatible with WACP-2 after SN:A526311)
  - Lens FOV 107-63°; Converted FOV 128-77°
  - **22140** N120 Extension Ring 40 II → **85206** N120/N100 WACP - 1B; **85201** N120 WACP - 1
    - On APS-C Sensor: Lens FOV 75-45°; Converted FOV 130-78°
    - On Full Frame Sensor: Lens FOV 75-63°; Converted FOV 130-109°; Zoom Range 28-35mm
  - **22150** N120 Extension Ring 50 II → **18809** 180mm Optical Glass Wide Angle Port
  - **22160** N120 Extension Ring 60 II → **18802** 8.5" Acrylic dome port; * **18812** 230mm Optical Glass Wide Angle Port

Sony SEL1635Z Vario-Tessar T* FE 16-35mm F4 ZA OSS
- **37145** SE1635-Z → **37401 + 37403** N100 Extension Ring 30 + N100 Extension Ring 50 → **37129** N100 180mm Optical Glass Wide Angle Port
- **37145 + 37146** SE1635-Z + SE1635-F → **37305** N100 to N120 35.5mm Port Adaptor II
  - **21110** N120 Extension Ring 10 → **85204** N120 WACP - 2 (* This setup is only compatible with WACP-2 before SN:A526311)
  - **22110** N120 Extension Ring 10 II → * **85204** N120 WACP - 2 (* This setup is only compatible with WACP-2 after SN:A526311)
  - Lens FOV 107-63°; Converted FOV 128-77°
  - **22150** N120 Extension Ring 50 II → **18809** 180mm Optical Glass Wide Angle Port
  - **22160** N120 Extension Ring 60 II → * **18812** 230mm Optical Glass Wide Angle Port

Sony FE PZ 16-35mm f/4 G
- **37172** SFE1635-Z
  - **37403** N100 Extension Ring 50 → **37129** N100 180mm Optical Glass Wide Angle Port
  - **37401 + 37401** N100 Extension Ring 30 + N100 Extension Ring 30 → **85205** N100 WACP - C — Lens FOV 75-63°; Converted FOV 130-109°; Zoom Range 28-35mm
  - **37305** N100 to N120 35.5mm Port Adaptor II
    - **22125** N120 Extension Ring 25 II → **18802** 8.5" Acrylic dome port; **18812** 230mm Optical Glass Wide Angle Port
    - **22120** N120 Extension Ring 20 II → **18809** 180mm Optical Glass Wide Angle Port
    - **22135** N120 Extension Ring 35 II → * **18815** 250mm Optical Glass Wide Angle Port
    - **21110** N120 Extension Ring 10 → **85201** N120 WACP - 1 (* This setup is only compatible with WACP-1 before SN: A502435)
    - **22110** N120 Extension Ring 10 II → **85201** N120 WACP - 1 (* This setup is only compatible with WACP-1 after SN: A502435); **85206** N120/N100 WACP - 1B
    - Lens FOV 75-63°; Converted FOV 130-109°; Zoom Range 28-35mm
  - **37306** N100 to N120 25mm Port Adaptor → * **85204** N120 WACP - 2 — Lens FOV 107-63°; Converted FOV 128-77°

Sony FE 24mm f/2.8 G
- **37130** N100 Flat Port 23 → **83250** M67 to Bayonet Mount Converter II → **83203** WWL-C — Lens FOV 84°; Converted FOV 130°

Sony FE 24mm f/1.4 GM
- **37305** N100 to N120 35.5mm Port Adaptor II
  - **22140** N120 Extension Ring 40 II → **18802** 8.5" Acrylic dome port; * **18809** 180mm Optical Glass Wide Angle Port
  - **85204** N120 WACP - 2 — Lens FOV 84°; Converted FOV 98°

Sony FE PZ 28-135mm f/4 G OSS
- **37169** SFE28135-Z / **37169 + 37170** STE28135-Z + STE28135-F → **37305** N100 to N120 35.5mm Port Adaptor II → **22190** N120 Extension Ring 90 II → **18812** 230mm Optical Glass Wide Angle Port

Sigma 14mm f/1.4 DG DN Art
- **37305** N100 to N120 35.5mm Port Adaptor II
  - **22160** N120 Extension Ring 60 II → **18809** 180mm Optical Glass Wide Angle Port (* This setup is only compatible with 18809 after SN: A512606)
  - **22170** N120 Extension Ring 70 II → **18802** 8.5" Acrylic dome port (* This setup is only compatible with 18802 after SN: A491459); **18812** 230mm Optical Glass Wide Angle Port; * **18815** 250mm Optical Glass Wide Angle Port
  - **22190** N120 Extension Ring 90 II → **85207** N120/N100 FCP - 1 — Circular Fisheye (remove shade); Converted FOV 180°; Zoom Range at 14mm only

Sigma 14mm f/1.8 DG HSM Art
- **37305** N100 to N120 35.5mm Port Adaptor II
  - **22160** N120 Extension Ring 60 II → **18809** 180mm Optical Glass Wide Angle Port
  - **22170** N120 Extension Ring 70 II → **18802** 8.5" Acrylic dome port; **18812** 230mm Optical Glass Wide Angle Port; * **18815** 250mm Optical Glass Wide Angle Port
  - **22190** N120 Extension Ring 90 II → **85207** N120/N100 FCP - 1 — Circular Fisheye (remove shade); Converted FOV 180°; Zoom Range at 14mm only

Sigma 15mm f/1.4 Fisheye DG DN Art
- **37305** N100 to N120 35.5mm Port Adaptor II → **22160** N120 Extension Ring 60 II
  - **18802** 8.5" Acrylic dome port (* This setup is only compatible with 18802 after SN: A491459; * AF-C focus mode is recommended to avoid focus shift issue)
  - **18812** 230mm Optical Glass Wide Angle Port (* AF-C focus mode is recommended to avoid focus shift issue)

Sigma 14-24mm F2.8 DG DN
- **19726** SLE1424-Z → **37305** N100 to N120 35.5mm Port Adaptor II
  - **22125** N120 Extension Ring 25 II → **85204** N120 WACP - 2 — Lens FOV 94-84°; Converted FOV 115-98°; Zoom Range 20-24mm
  - **22140** N120 Extension Ring 40 II → **18809** 180mm Optical Glass Wide Angle Port; **18812** 230mm Optical Glass Wide Angle Port
  - **22150** N120 Extension Ring 50 II → * **18815** 250mm Optical Glass Wide Angle Port
  - **22155** N120 Extension Ring 55 II → **85207** N120/N100 FCP - 1 — Circular Fisheye (remove shade); Converted FOV 180°; Zoom Range at 14mm only
  - **22160** N120 Extension Ring 60 II → **18802** 8.5" Acrylic dome port
- **19726 + 19727** SLE1424-Z + SLE1424-F → **37305** N100 to N120 35.5mm Port Adaptor II → **22150 + 22151** N120 Extension Ring 50 II + Focus Knob → **18812** 230mm Optical Glass Fisheye Port II

Sigma 24mm f/3.5 DG DN
- **37127** N100 Flat Port 32 → **83250** M67 to Bayonet Mount Converter II → **83203** WWL-C — Lens FOV 84°; Converted FOV 130°
- **37403** N100 Extension Ring 50 → * **37129** N100 180mm Optical Glass Wide Angle Port
- **37305** N100 to N120 35.5mm Port Adaptor II → **22120** N120 Extension Ring 20 II → **18809** 180mm Optical Glass Wide Angle Port

Tamron 17-28mm f/2.8 Di III RXD
- **37157** STE1728-Z → **37305** N100 to N120 35.5mm Port Adaptor II → **85204** N120 WACP - 2 — Lens FOV 104-75°; Converted FOV 123-89°
- **37157 + 37158** STE1728-Z + STE1728-F → **37305** N100 to N120 35.5mm Port Adaptor II → **22140** N120 Extension Ring 40 II → **18802** 8.5" Acrylic dome port; * **18809** 180mm Optical Glass Wide Angle Port; **18812** 230mm Optical Glass Wide Angle Port

Tamron 20-40mm f/2.8 Di III VXD
- **37177** STE2040-Z
  - **37403** N100 Extension Ring 50
    - **85205** N100 WACP - C (* AF-C focus mode is recommended to avoid focus shift issue)
    - **85206** N120/N100 WACP - 1B (* AF-C focus mode is recommended to avoid focus shift issue)
    - **85203** N100 WACP - 1 (* AF-C focus mode is recommended to avoid focus shift issue)
    - Lens FOV 75-56.5°; Converted FOV 130-98°; Zoom Range 28-40mm
  - **37401 + 37401** N100 Extension Ring 30 + N100 Extension Ring 30 → **85207** N120/N100 FCP - 1 (* slight vignetting at 28mm; * AF-C focus mode is recommended to avoid focus shift issue) — Lens FOV 75-56.5°; Converted FOV 170-110°; Zoom Range 28-40mm
  - **37402 + 37408** N100 Extension Ring 40 + N100 Extension Ring 35 → **37129** N100 180mm Optical Glass Wide Angle Port
  - **37305** N100 to N120 35.5mm Port Adaptor II
    - **22120** N120 Extension Ring 20 II → **85206** N120/N100 WACP - 1B (* AF-C focus mode is recommended to avoid focus shift issue); **85201** N120 WACP - 1 (* AF-C focus mode is recommended to avoid focus shift issue) — Lens FOV 75-56.5°; Converted FOV 130-98°; Zoom Range 28-40mm
    - **22125** N120 Extension Ring 25 II → **85207** N120/N100 FCP - 1 (* slight vignetting at 28mm; * AF-C focus mode is recommended to avoid focus shift issue) — Lens FOV 75-56.5°; Converted FOV 170-110°; Zoom Range 28-40mm
    - **22140** N120 Extension Ring 40 II → **18809** 180mm Optical Glass Wide Angle Port; **18802** 8.5" Acrylic dome port; **18812** 230mm Optical Glass Wide Angle Port

Zeiss Batis 18mm F/2.8
- **37305** N100 to N120 35.5mm Port Adaptor II → **22120** N120 Extension Ring 20 II → **18809** 180mm Optical Glass Wide Angle Port

Sony FE 28mm f/2 + Sony 21mm Ultra-Wide Conversion Lens
- **37305** N100 to N120 35.5mm Port Adaptor II → **22130** N120 Extension Ring 30 II → **18809** 180mm Optical Glass Wide Angle Port

Sony FE 28mm f/2 + Sony 16mm Fisheye Conversion Lens
- **37305** N100 to N120 35.5mm Port Adaptor II → **22130** N120 Extension Ring 30 II → **18810** 140mm Optical Glass Wide Angle Port

Sony Full Frame Camera Sensor
- **36317** Filter Holder → **37202** Nikonos Adaptor → U/W Nikkor 15 mm f/2.8; U/W Nikkor 20 mm f/2.8; U/W Nikkor 80mm f/1.4; Sea & Sea 12mm f/3.5 Fisheye for Nikonos

CANON EF-MOUNT

Sigma 15mm F2.8 EX DG Diagonal Fisheye with Metabones T Smart Adaptor III/IV/V
- **19546** SC15-F → **37305** N100 to N120 35.5mm Port Adaptor II → **18810** 140mm Optical Glass Fisheye Port

Other Canon EF-mount Lenses with Metabones T Smart Adaptor III/IV/V
- **37305** N100 to N120 35.5mm Port Adaptor II → **N120 Canon EF-Mount Port System**

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System