



WET WIDE LENS FOR COMPACT CAMERAS (WWL-C)
130 DEG. FOV WITH COMPATIBLE 24MM LENSES

| | CAMERA LENS | GEAR | PORT | MOUNT CONVERTER | WET LENS | OPTICAL PERFORMANCE | | |
|--|--|--|---|--|--|--|---|---|
| N120 CINEMA SYSTEM (RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC) | STANDARD ZOOM FULL FRAME | Canon RF 24-50mm f/4.5-6.3 IS STM | 16347 RF2450 Gear Set | 18709 N120 Flat Port 27 with Bayonet Mount <i>* Unlock the lens before entering the camera into housing</i> | 83203 WWL-C | Lens FOV Converted FOV | 84-46.8° 130-72° | |
| | | N120 NIKON Z-MOUNT | Nikkor Z 24-50mm f/4-6.3 Lens | 19163 NZ2450-Z | 18707 N120 Macro Port 6 | 83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i> | 83203 WWL-C | Lens FOV Converted FOV |
| N120 CANON RF-MOUNT | STANDARD ZOOM FULL FRAME | Canon RF 24-50mm f/4.5-6.3 IS STM | 19598 CR2450-Z | 18709 N120 Flat Port 27 with Bayonet Mount <i>* Unlock the lens before entering the camera into housing</i> | 83203 WWL-C | Lens FOV Converted FOV | 84-46.8° 130-72° | |
| | | WIDE ANGLE FULL FRAME | Canon RF 24mm f/1.8 Macro IS STM | 18707 N120 Macro Port 6 | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV | 84° 130° |
| N100 FUJIFILM X-MOUNT | STANDARD ZOOM APSC | Fujifilm XC 15-45mm f/3.5-5.6 OIS PZ | 36476 X1545PZ-Z | 36478 N100 Flat Port 40 | 83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i> | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 84-35° 130-54° 16-45mm |
| N100 CANON RF-MOUNT | STANDARD ZOOM APSC | Canon RF-S 18-45mm f/4.5-6.3 IS STM | 19596 CRS1845-Z | 37181 N100 Flat Port 50 | 83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i> | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 75-35° 116-52° 18-45mm |
| N100 NIKON Z-MOUNT | STANDARD ZOOM DX | NIKKOR Z DX 16-50mm f/3.5-6.3 VR | 37602 Z1650PZ-Z | 37601 N100 Flat Port 29 | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV | 84-31.5° 130-49° |
| N100 SONY E-MOUNT | WIDE ANGLE FULL FRAME | Sony FE 24mm f/2.8 G | 37130 | N100 Flat Port 23 | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV | 84° 130° |
| | | Sigma 24mm f/3.5 DG DN | 37127 | N100 Flat Port 32 | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV | 84° 130° |
| N85 MICRO FOUR THIRDS SYSTEM | STANDARD ZOOM FOUR THIRDS | Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ | 36147 O1250-Z <i>* 36059 O1250-Z for NA-GH5 & NA-EM1X</i> | 36161 N85 Macro Port with M77 Thread <i>* 36167 Gear Set for NA-OM1</i> | 83251 M77 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 72-24° 110-37° 14-50mm |
| | | Panasonic LUMIX G VARIO 12-32mm F3.5-5.6 ASPH. ASPH. MEGA O.I.S. | 36046 P1232-Z | 36165 N85 Power Zoom Macro Port 29 | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV | 84-37° 130-57° |
| N85 SONY E-MOUNT | WIDE ANGLE FOUR THIRDS | Olympus M.ZUIKO DIGITAL ED 12mm f/2.0 | 36168 | N85 Pancake Port 24 | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV | 84° 130° |
| | | STANDARD ZOOM APSC | Sony E PZ 16-50mm f/3.5-5.6 OSS | 36172 SE1650-PZ | 36228 N85 Macro Port 40 with Knob | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV Zoom Range |
| N85 CANON EF-M-MOUNT | STANDARD ZOOM APSC | Canon EF-M 15-45mm f/3.5-6.3 IS STM | 36195 CM1545-Z | 36135 N85 Macro Port 45 | 83250 M67 to Bayonet Mount Converter II | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 76-33° 117-51° 17-45mm |
| N50 & COMPACT SYSTEM | SONY | Sony Cyber-shot DSC-RX100 Mark V (17418/17418P NA-RX100V / Pro Package) | | | 83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i> | 83203 WWL-C | Lens FOV Converted FOV | 84-34° 130-52° |
| | | * 24-70mm (35mm equivalent) | | | | | | |
| | | * Port is inexchangeable for this housing | | | | | | |
| | Sony Cyber-shot DSC-RX100 Mark VI (17421/17421P NA-RX100VI / Pro Package) | | | 38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i> | | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 84-46° 130-70° 24-50mm |
| | * 24-200mm (35mm equivalent) | | | | | | | |
| | * Port is inexchangeable for this housing | | | | | | | |
| | Sony Cyber-shot DSC-RX100 Mark VII (17424/17424P NA-RX100VII / Pro Package) | | | 38705 N50 Short Port 17 with Bayonet Mount <i>* change port from housing</i> | | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 84-46° 130-70° 24-30mm |
| | * 24-200mm (35mm equivalent) | | | | | | | |
| | * Port is inexchangeable for this housing | | | | | | | |
| CANON | Canon Powershot G5XMKII (17331/17331P NA-G5XII / Pro Package) | | | 38703 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i> | | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 84-46° 130-71° 24-50mm |
| | * 24-120mm (35mm equivalent) | | | | | | | |
| | * Port is inexchangeable for this housing | | | | | | | |
| Canon Powershot G7XMKII (17324 NA-G7XII) | | | 38703 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i> | | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 84-46° 130-71° 24-50mm | |
| * 24-100mm (35mm equivalent) | | | | | | | | |
| * Port is inexchangeable for this housing | | | | | | | | |
| Canon Powershot G7XMKIII (17330/17330P NA-G7XIII / Pro Package) | | | 38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i> | | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 84-46° 130-71° 24-50mm | |
| * 24-100mm (35mm equivalent) | | | | | | | | |
| * Port is inexchangeable for this housing | | | | | | | | |
| PANASONIC | Panasonic Lumix DC-LX100II (17717 NA-LX100II) | | | 38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i> | | 83203 WWL-C | Lens FOV Converted FOV Working Distance | 84-72° 130-112° 24-30mm |
| | * 24-75mm (35mm equivalent) | | | | | | | |
| * Port is inexchangeable for this housing | | | | | | | | |
| Panasonic Lumix DC-LX10 (LX15) (17714 NA-LX10) | | | | 83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i> | | 83203 WWL-C | Lens FOV Converted FOV Zoom Range | 70-34° 108-53° 32-72mm |
| * 24-72mm (35mm equivalent) | | | | | | | | |
| * Port is inexchangeable for this housing | | | | | | | | |
| OLYMPUS | Olympus Tough TG5/TG6/TG7 (with M52 Thread) | | | | 83255 M52 to Bayonet Mount Converter | 83203 WWL-C | Lens FOV Converted FOV | 84-24° 130-37° |
| | * 24-100mm (35mm equivalent) | | | | | | | |
| | * Port is inexchangeable for this housing | | | | | | | |
| Olympus Tough TG5/TG6/TG7 (with Bayonet Mount) | | | | | 83203 WWL-C | Lens FOV Converted FOV | 84-24° 130-37° | |
| * 24-100mm (35mm equivalent) | | | | | | | | |
| * Port is inexchangeable for this housing | | | | | | | | |
| Olympus PT-058/ PT-059 Underwater Housing | | | | 83256 Bayonet Mount Converter for Olympus PT-058/PT-059 | 83203 WWL-C | Lens FOV Converted FOV | 84-24° 130-37° | |

83203
WET WIDE LENS FOR COMPACT CAMERAS (WWL-C)
130 deg. FOV with compatible 24mm lenses

Specifications

| | | |
|-----------------------------|---|--|
| Dimension (mm) | : | DIA156mm x 78mm |
| Weight in Air | : | 1.05kg |
| Buoyancy in Water | : | Negative 0.17 kg |
| Body Construction | : | Hard-anodized aluminum alloy |
| Lens Construction | : | 4 Elements |
| Lens Coating | : | Anti-reflective on both sides |
| Focus Distance | : | From front element of lens to infinity |
| Maximum FOV (underwater) | : | 130° (Ref. 24mm equivalent) |
| Lens Mount | : | Bayonet Mount |
| Depth Rating | : | 100m |
| Pre-installed | : | Integrated aluminium float collar |

Package includes

- WWL-C with Bayonet Mount
- Front hard lens cap
- Rear lens caps
- Padded carrying bag
- Cleaning Cloth
- Lubricant