



N100 PORT SYSTEM FOR NIKON Z-MOUNT CAMERA SYSTEM (DX & F-Mount Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
MACRO DX	NIKKOR Z MC 50mm f/2.8 Macro			37401 / 37430 N100 Extension Ring 30 / N100 Extension Ring 30 II	37601 N100 Flat Port 29	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL-1	Lens FOV	31.5°
					37124 Flat port 66 with M77 Thread	83251 M77 to Bayonet Mount Converter II			
STANDARD ZOOM DX	NIKKOR Z DX 16-50mm f/3.5-6.3 VR	37602 Z1650PZZ			37601 N100 Flat Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC-1	Max. Magnification	0.9X
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC			
						83250 M67 to Bayonet Mount Converter II	* 83203 WWL-C	Lens FOV	84-31.5°
							83202 WWL-1B	Converted FOV	130-49°
NIKON F-MOUNT	Nikon F-mount Lenses with Nikon Adaptor FTZ		37305 N100 to N120 35.5mm Port Adaptor II		N120 Nikon F-Mount Port System			Lens FOV	72-31.5°
	* It is required to replace tripod socket cover of Nikon adaptor FTZ by #25220 Tripod socket replacement							Converted FOV	125-55°
								Zoom Range	20-50mm

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System

Last Updated : 2024-07-24

* This port chart is subject to updating as new information becomes available