



N120 PORT SYSTEM FOR FUJIFILM G-MOUNT CAMERA SYSTEM (Medium Format Lens)

	CAMERA LENS	GEAR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO MEDIUM FORMAT	Fujifilm GF 120mm f/4 Macro R LM OIS WR	19823 GF120-F	22160 N120 Extension Ring 60 II	18701 Macro Port 60	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i> SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 2.0X Working Distance 65-93mm
	Fujifilm GF 120mm f/4 Macro R LM OIS WR with HOYA +2 Close Up Diopter	19823 GF120-F	22170 N120 Extension Ring 70 II	18701 Macro Port 60	83250 M67 to Bayonet Mount Converter II	87302 EMWL Set #2	Lens FOV 25.7° Converted FOV 60°/100°/130°/160°
	Laowa 17mm f/4 GFX Zero-D	19824 + 19825 GL17-A + GL17-F	22135 + 22151 N120 Extension Ring 35 II + Focus Knob 22135 + 22140 N120 Extension Ring 35 II + 40 II 22135 + 22150 N120 Extension Ring 35 II + 50 II	85204 N120 WACP - 2 * 18815 250mm Optical Glass Wide Angle Port II 18812 230mm Optical Glass Wide Angle Port II			Lens FOV 114° Converted FOV 140°
STANDARD ZOOM MEDIUM FORMAT	Fujifilm GF 63mm f/2.8 R WR			18701 Macro Port 60			
	Fujifilm GF 35-70mm f/4.5-5.6 WR		22170 N120 Extension Ring 70 II	18802 8.5" Acrylic Dome Port <i>* Minimum focus distance from port to subject is 0.40m at 35mm and 0.32m at 70mm</i> 18809 180mm Optical Glass Wide Angle Port <i>* Minimum focus distance from port to subject is 0.40m at 35mm and 0.27m at 70mm</i> 18812 230mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.40m at 35mm and 0.33m at 70mm</i>			
			22180 N120 Extension Ring 80 II	* 18815 250mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.30m at 35mm and 0.20m at 70m</i>			
			22140 N120 Extension Ring 40 II	* 85206 N120/N100 WACP - 1B 85201 N120 WACP - 1			Lens FOV 76-42.7° Converted FOV 131.5-74° <i>* Minimum focus distance from port to subject is 0.20m at 35mm and 0.10m at 70mm</i>
	19826 GF3570-Z		22150 N120 Extension Ring 50 II	85207 N120/N100 FCP - 1		Lens FOV 75-43° Converted FOV 170-80°	
WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 20-35mm F4 R WR	19827 GF2035-Z	22135 N120 Extension Ring 35 II 22170 N120 Extension Ring 70 II 22180 N120 Extension Ring 80 II	85204 N120 WACP - 2 18809 180mm Optical Glass Wide Angle Port 18802 8.5" Acrylic Dome Port 18812 230mm Optical Glass Wide Angle Port II * 18815 250mm Optical Glass Wide Angle Port II			Lens FOV 108-76° Converted FOV 132-93°
	Fujifilm GF 23mm F4 R LM WR		22120 N120 Extension Ring 20 II 22160 N120 Extension Ring 60 II	85204 N120 WACP - 2 18812 230mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.38m</i> * 18815 250mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.24m</i>			Lens FOV 100° Converted FOV 118°
	Fujifilm GF 32-64mm f/4 R LM WR	19822 GF3264-Z	22140 + 22160 N120 Extension Ring 40 II + 60 II	* 18815 250mm Optical Glass Wide Angle Port II <i>* Minimum focus distance from port to subject is 0.50m</i> 18805 10" Acrylic Wide Angle Port <i>* Minimum focus distance from port to subject is 0.45m</i>			
	Fujifilm GF 45mm f/2.8 R WR			18701 Macro Port 60 22130 N120 Extension Ring 30 II	* 85206 N120/N100 WACP - 1B 85201 N120 WACP - 1		Lens FOV 63° Converted FOV 109°
CANON EF-MOUNT (with Metabones EF-GFX mount Smart Expander 1.26x) FULL FRAME	Canon EF 100mm f/2.8L Macro IS USM	TBD CGF100IS-F	22130 N120 Extension Ring 30 II	18703 Macro Port 94	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i> SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1 81202 SMC - 2	Max. Magnification 2.8X Working Distance 44-93mm Max. Magnification 4.5X Working Distance 21-37mm
	Canon EF 28-70mm f/3.5-4.5 II	TBD CGF2870F3.5II-Z	22150 N120 Extension Ring 50 II	* 85206 N120/N100 WACP - 1B 85201 N120 WACP - 1			Lens FOV 75-34° Converted FOV 130-59°
	Canon EF 16-35mm f/2.8 III USM	TBD CGF1635III-Z	22180 N120 Extension Ring 80 II 22190 + 22130 N120 Extension Ring 90 II + 30 II	85204 N120 WACP - 2 18802 8.5" Acrylic Dome Port * 18812 230mm Optical Glass Wide Angle Port II 18815 250mm Optical Glass Wide Angle Port II			Lens FOV 107-63° Converted FOV 128-72°
	Canon EF 16-35mm f/4 IS USM	TBD CGF1635I4-Z	22160 N120 Extension Ring 60 II 22170 + 22130 N120 Extension Ring 70 II + 30 II 22180 + 22130 N120 Extension Ring 80 II + 30 II	85204 N120 WACP - 2 18802 8.5" Acrylic Dome Port * 18812 230mm Optical Glass Wide Angle Port II 18815 250mm Optical Glass Wide Angle Port II			Lens FOV 107-63° Converted FOV 128-72°

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System

Last Updated : 2024-07-24

* This port chart is subject to updating as new information becomes available