



COMPACT & N50 PORT SYSTEM FOR COMPACT CAMERA SYSTEM

	CAMERA (HOUSING)	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE					
SONY	Sony Cyber-shot DSC-RX100 Mark V (17418/17418P NA-RX100V / Pro Package) * 24-70mm (35mm equivalent) * Port is inexchangeable for this housing		SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 35 x 23.3 mm 55-75 mm					
			SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC			81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 48 x 32mm 80-124 mm			
			83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL - C 83202 WWL - 1B 86201 MWL - 1	Lens FOV Converted FOV 84-34° 130-52° Lens FOV Converted FOV Zoom Range 75-34° 130-58° 28-70 mm Lens FOV Converted FOV Zoom Range 37-34° 138-128° 65-70 mm					
	Sony Cyber-shot DSC-RX100 Mark VI (17421/17421P NA-RX100VI / Pro Package) * 24-200mm (35mm equivalent) * Port is exchangeable for this housing		38702 N50 3.5" Acrylic Wide Angle Dome Port	25107 M67 Flip Diopter Holder	81201 SMC - 1 81202 SMC - 2	Smallest Subject Size Working Distance 14 x 9.3 mm 84-94 mm Smallest Subject Size Working Distance 7.5 x 5 mm 34-37 mm				
							38704 N50 Short Port 22 with Bayonet Mount * change port from housing	83203 WWL - C 81301 CMC - 1 81302 CMC - 2	Lens FOV Converted FOV Zoom Range 84-46° 130-70° 24-50 mm Smallest Subject Size Working Distance 38 x 25.3 mm 25-95 mm Smallest Subject Size Working Distance 48.5 x 32.3 mm 50-160 mm	
			38703 N50 Short Port 25 with Bayonet Mount * change port from housing	86201 MWL - 1 83202 WWL - 1B	Lens FOV Converted FOV Zoom Range 40-37° 150-138° 60-65 mm Lens FOV Converted FOV Zoom Range 75-37° 130-64° 28-65 mm					
			Sony Cyber-shot DSC-RX100 Mark VII (17424/17424P NA-RX100VII / Pro Package) * 24-200mm (35mm equivalent) * Port is exchangeable for this housing		38702 N50 3.5" Acrylic Wide Angle Dome Port	25107 M67 Flip Diopter Holder	81201 SMC - 1 81202 SMC - 2	Smallest Subject Size Working Distance 14 x 9.3 mm 84-94 mm Smallest Subject Size Working Distance 7.5 x 5 mm 34-37 mm		
									38705 N50 Short Port 17 with Bayonet Mount * change port from housing	83203 WWL - C 81301 CMC - 1 81302 CMC - 2
					38703 N50 Short Port 25 with Bayonet Mount * change port from housing	86201 MWL - 1 83202 WWL - 1B	Lens FOV Converted FOV Zoom Range 37° 138° 65 mm Lens FOV Converted FOV Zoom Range 75-37° 130-64° 28-65 mm			
	83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2			Smallest Subject Size Working Distance 34 x 22.7 mm 40-85 mm Smallest Subject Size Working Distance 43.5 x 29 mm 58-154 mm					
		CANON	Canon Powershot G5XMKII (17331/17331P NA-G5XII / Pro Package) * 24-120mm (35mm equivalent) * Port is exchangeable for this housing		38702 N50 3.5" Acrylic Wide Angle Dome Port	25107 M67 Flip Diopter Holder	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 21 x 14 mm 44-72 mm Smallest Subject Size Working Distance 21x18mm 67-120mm Smallest Subject Size Working Distance 24x16mm 58-93mm		
	38703 N50 Short Port 25 with Bayonet Mount * change port from housing								83203 WWL - C 83202 WWL - 1B	Lens FOV Converted FOV Zoom Range 84-46° 130-71° 24-50mm Lens FOV Converted FOV Zoom Range 75-46° 130-89° 28-50mm
	83214 Bayonet Mount Adaptor for SMC/CMC				81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 40x26.7mm 20-72mm Smallest Subject Size Working Distance 47x31.3mm 33-122mm				
	Canon Powershot G7XMKII (17324 NA-G7XII) * 24-100mm (35mm equivalent) * Port is exchangeable for this housing			38702 N50 3.5" Acrylic Wide Angle Dome Port	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 23x13.3mm 56-72mm Smallest Subject Size Working Distance 31x20.7mm 87-122mm			
								SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification Working Distance 25.5x17mm 73-93mm
83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>				86201 MWL - 1	Lens FOV Converted FOV Zoom Range 37-24° 138-99° 65-100mm					
38703 N50 Short Port 25 with Bayonet Mount * change port from housing				83203 WWL - C 83202 WWL - 1B	Lens FOV Converted FOV Zoom Range 84-46° 130-71° 24-50mm Lens FOV Converted FOV Zoom Range 75-37° 130-64° 28-65mm					
						83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 23x13.3mm 45-72mm Smallest Subject Size Working Distance 31x20.7mm 66-122mm		
							38702 N50 3.5" Acrylic Wide Angle Dome Port	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 23x13.3mm 56-72mm Smallest Subject Size Working Distance 31x20.7mm 87-122mm
	SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC		81201 SMC - 1			Max. Magnification Working Distance 25.5x17mm 73-93mm				
83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1			Lens FOV Converted FOV Zoom Range 37-24° 138-99° 65-100mm						
Canon Powershot G7XMKIII (17330/17330P NA-G7XIII / Pro Package) * 24-100mm (35mm equivalent) * Port is exchangeable for this housing			38702 N50 3.5" Acrylic Wide Angle Dome Port	25107 M67 Flip Diopter Holder	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 23x13.3mm 56-72mm Smallest Subject Size Working Distance 31x20.7mm 87-122mm				
							38703 N50 Short Port 25 with Bayonet Mount * change port from housing	83203 WWL - C 83202 WWL - 1B	Lens FOV Converted FOV Zoom Range 84-46° 130-71° 24-50mm Lens FOV Converted FOV Zoom Range 75-37° 130-64° 28-65mm	
			83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 33x22mm 45-72mm Smallest Subject Size Working Distance 41x27.3mm 66-122mm					
				38704 N50 Short Port 22 with Bayonet Mount * change port from housing	83203 WWL - C 83202 WWL - 1B	Lens FOV Converted FOV Zoom Range 84-46° 130-71° 24-50mm Lens FOV Converted FOV Zoom Range 75-46° 130-89° 28-50mm				
			83214 Bayonet Mount Adaptor for SMC/CMC				81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 33x22mm 45-72mm Smallest Subject Size Working Distance 41x27.3mm 66-122mm		
							PANASONIC	Panasonic Lumix DC-LX100II (17717 NA-LX100II) * 24-75mm (35mm equivalent) * Port is exchangeable for this housing		38702 N50 3.5" Acrylic Wide Angle Dome Port
38703 N50 Short Port 25 with Bayonet Mount * change port from housing	83202 WWL - 1B		Lens FOV Converted FOV Zoom Range 75-57° 130-99° 28-40mm							
83214 Bayonet Mount Adaptor for SMC/CMC		83203 WWL - C 83202 WWL - 1B		Lens FOV Converted FOV Zoom Range 84-72° 130-112° 24-30mm Lens FOV Converted FOV Zoom Range 75-72° 130-125° 28-30mm						
	Panasonic Lumix DC-LX10I (17714 NA-LX10) * 24-75mm (35mm equivalent) * Port is inexchangeable for this housing		38702 N50 3.5" Acrylic Wide Angle Dome Port	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 34x22.7mm 48-73mm Smallest Subject Size Working Distance 46x30.7mm 76-128mm				
SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC								81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 34x22.7mm 48-73mm Smallest Subject Size Working Distance 46x30.7mm 76-128mm	
83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>			83203 WWL - C 83202 WWL - 1B 86201 MWL - 1	Lens FOV Converted FOV Zoom Range 70-34° 108-53° 32-72mm Lens FOV Converted FOV Zoom Range 58-34° 100-60° 38-72mm Lens FOV Converted FOV Zoom Range 37-34° 138-128° 65-72mm						
OLYMPUS	Olympus Tough TG5/TG6/TG7 (with M52 Thread) * 24-100mm (35mm equivalent) * Port is inexchangeable for this housing		83255 M52 to Bayonet Mount Converter	83203 WWL - C	Lens FOV Converted FOV 84-24° 130-37°					
						SMC/CMC Option 1 - M67 Thread 38024 + 81228 M52 to M67 Step Up Adaptor Ring + M67 Spacer Ring for SMC/CMC <i>(81228 is included in all SMC/CMC)</i>	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 19x12.7mm 34-78mm Smallest Subject Size Working Distance 21x14mm 28.5-98mm		
			SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2	Smallest Subject Size Working Distance 19x12.7mm 34-78mm Smallest Subject Size Working Distance 21x14mm 28.5-98mm					
	Olympus Tough TG5/TG6/TG7 (with Bayonet Mount) * 24-100mm (35mm equivalent) * Port is inexchangeable for this housing		83203 WWL - C			Lens FOV Converted FOV 84-24° 130-37°				
				83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2		Smallest Subject Size Working Distance 19x12.7mm 34-78mm Smallest Subject Size Working Distance 21x14mm 28.5-98mm			
			83255 M52 to Bayonet Mount Converter	83203 WWL - C		Lens FOV Converted FOV 84-24° 130-37°				
OLYMPUS	Olympus PT-058/PT-059 Underwater Housing	83256 Bayonet Mount Converter for Olympus PT-058/PT-059	83203 WWL - C		Lens FOV Converted FOV 84-24° 130-37°					

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System