



**WET WIDE LENS FOR COMPACT CAMERAS (WWL-C)**  
130 DEG. FOV WITH COMPATIBLE 24MM LENSES

	CAMERA LENS	GEAR	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE		
N120 CINEMA SYSTEM (RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC)	STANDARD ZOOM FULL FRAME	Canon RF 24-50mm f/4.5-6.3 IS STM	16347 RF2450 Gear Set	18709 N120 Flat Port 27 with Bayonet Mount <i>* Unlock the lens before entering the camera into housing</i>	83203 WWL-C	Lens FOV Converted FOV	84-46.8° 130-72°	
	STANDARD ZOOM FX	Nikkor Z 24-50mm f/4-6.3 Lens	19163 NZ2450-Z	18707 N120 Macro Port 6	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV	84-47° 130-72°
N120 CANON RF-MOUNT	STANDARD ZOOM FULL FRAME	Canon RF 24-50mm f/4.5-6.3 IS STM	19598 CR2450-Z	18709 N120 Flat Port 27 with Bayonet Mount <i>* Unlock the lens before entering the camera into housing</i>	83203 WWL-C	Lens FOV Converted FOV	84-46.8° 130-72°	
	WIDE ANGLE FULL FRAME	Canon RF 24mm f/1.8 Macro IS STM		18707 N120 Macro Port 6	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV	84° 130°
N100 FUJIFILM X-MOUNT	STANDARD ZOOM APSC	Fujifilm XC 15-45mm f/3.5-5.6 OIS PZ	36476 X1545PZ-Z	36478 N100 Flat Port 40	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV Zoom Range	84-35° 130-54° 16-45mm
N100 CANON RF-MOUNT	STANDARD ZOOM APSC	Canon RF-S 18-45mm f/4.5-6.3 IS STM	19596 CRS1845-Z	37181 N100 Flat Port 50	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV Zoom Range	75-35° 116-52° 18-45mm
N100 NIKON Z-MOUNT	STANDARD ZOOM DX	NIKKOR Z DX 16-50mm f/3.5-6.3 VR	37602 Z1650PZ-Z	37601 N100 Flat Port 29	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV	84-31.5° 130-49°
N100 SONY E-MOUNT	WIDE ANGLE FULL FRAME	Sony FE 24mm f/2.8 G		37130 N100 Flat Port 23	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV	84° 130°
	WIDE ANGLE FULL FRAME	Sigma 24mm f/3.5 DG DN		37127 N100 Flat Port 32	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV	84° 130°
N85 MICRO FOUR THIRDS SYSTEM	STANDARD ZOOM FOUR THIRDS	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36147 O1250-Z <i>* 36059 O1250-Z for NA-GH5 &amp; NA-EM1X</i>	36161 N85 Macro Port with M77 Thread <i>* 36167 Gear Set for NA-OM1</i>	83251 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV Zoom Range	72-24° 110-37° 14-50mm
	STANDARD ZOOM FOUR THIRDS	Panasonic LUMIX G VARIO 12-32mm F3.5-5.6 ASPH. ASPH. MEGA O.I.S.	36046 P1232-Z	36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV	84-37° 130-57°
	WIDE ANGLE FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 12mm f/2.0		36168 N85 Pancake Port 24	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV	84° 130°
N85 SONY E-MOUNT	STANDARD ZOOM APSC	Sony E PZ 16-50mm f/3.5-5.6 OSS	36172 SE1650-PZ	36228 N85 Macro Port 40 with Knob	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV Zoom Range	80-31° 124-48° 17-50mm
N85 CANON EF-M-MOUNT	STANDARD ZOOM APSC	Canon EF-M 15-45mm f/3.5-6.3 IS STM	36195 CM1545-Z	36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV Zoom Range	76-33° 117-51° 17-45mm
N50 & COMPACT SYSTEM	SONY	Sony Cyber-shot DSC-RX100 Mark V (17418/17418P NA-RX100V / Pro Package)			83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV	84-34° 130-52°
		* 24-70mm (35mm equivalent)						
		<i>* Port is inexchangeable for this housing</i>						
	Sony Cyber-shot DSC-RX100 Mark VI (17421/17421P NA-RX100VI / Pro Package)			38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range	84-46° 130-70° 24-50mm
	* 24-200mm (35mm equivalent)							
	<i>* Port is exchangeable for this housing</i>							
	Sony Cyber-shot DSC-RX100 Mark VII (17424/17424P NA-RX100VII / Pro Package)			38705 N50 Short Port 17 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range	84-46° 130-70° 24-30mm
	* 24-200mm (35mm equivalent)							
	<i>* Port is exchangeable for this housing</i>							
	CANON	Canon Powershot G5XMKII (17331/17331P NA-G5XII / Pro Package)			38703 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range
* 24-120mm (35mm equivalent)								
<i>* Port is exchangeable for this housing</i>								
Canon Powershot G7XMKII (17324 NA-G7XII)			38703 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm	
* 24-100mm (35mm equivalent)								
<i>* Port is exchangeable for this housing</i>								
Canon Powershot G7XMKIII (17330/17330P NA-G7XIII / Pro Package)			38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm	
* 24-100mm (35mm equivalent)								
<i>* Port is exchangeable for this housing</i>								
PANASONIC	Panasonic Lumix DC-LX100II (17717 NA-LX100II)			38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Working Distance	84-72° 130-112° 24-30mm
	* 24-75mm (35mm equivalent)							
<i>* Port is exchangeable for this housing</i>								
Panasonic Lumix DC-LX10 (LX15) (17714 NA-LX10)				83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range	70-34° 108-53° 32-72mm
* 24-72mm (35mm equivalent)								
<i>* Port is inexchangeable for this housing</i>								
OLYMPUS	Olympus Tough TG5/TG6/TG7 (with Bayonet Mount)					83203 WWL-C	Lens FOV Converted FOV	84-24° 130-37°
	* 24-100mm (35mm equivalent)							
<i>* Port is inexchangeable for this housing</i>								
Olympus PT-058/ PT-059 Underwater Housing				83256 Bayonet Mount Converter for Olympus PT-058/PT-059		83203 WWL-C	Lens FOV Converted FOV	84-24° 130-37°

**83203**  
**WET WIDE LENS FOR COMPACT CAMERAS (WWL-C)**  
130 deg. FOV with compatible 24mm lenses

**Specifications**

Dimension (mm)	:	DIA156mm x 78mm
Weight in Air	:	1.05kg
Buoyancy in Water	:	Negative 0.17 kg
Body Construction	:	Hard-anodized aluminum alloy
Lens Construction	:	4 Elements
Lens Coating	:	Anti-reflective on both sides Multi-layer Broad-band
Focus Distance	:	From front element of lens to infinity
Maximum FOV (underwater)	:	130° (Ref. 24mm equivalent)
Lens Mount	:	Bayonet Mount
Depth Rating	:	100m
Pre-installed	:	Integrated aluminium float collar

**Package includes**

- WWL-C with Bayonet Mount
- Front hard lens cap
- Rear lens caps
- Padded carrying bag
- Cleaning Cloth
- Lubricant