



N100 PORT SYSTEM FOR Canon RF-S CAMERA SYSTEM (RF-S & EF-Mount Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE				
STANDARD ZOOM APSC	Canon RF-S 18-45mm f4.5-6.3 IS STM	19596 CR1845-Z			37181 N100 Flat Port 50	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 44-81mm				
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC		81302 CMC - 2	Max. Magnification 0.6X Working Distance 68-140mm			
											* 83202 WWL - 1B	Lens FOV 75-35° Converted FOV 130-60° Zoom Range 18-45mm
											83203 WWL - C	Lens FOV 75-35° Converted FOV 116-52° Zoom Range 18-45mm
											86201 MWL - 1	Lens FOV 40-35° Converted FOV 150-130° Zoom Range 38-45mm
									37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	* 85206 N120/N100 WACP - 1B		
										85203 N100 WACP-1		
										85205 N100 WACP - C		Lens FOV 75-35° Converted FOV 130-60°
									37305 N100 to N120 35.5mm Port Adaptor II <i>* This setup is only compatible with 37305 after SN:A544975, older version 37305 can be upgraded using lock mechanism 95851</i>	85206 N120/N100 WACP - 1B		
										85201 N120 WACP - 1		
				37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	85207 N120/N100 FCP-1		Lens FOV 74-34° Converted FOV 170-62°					
WIDE ANGLE APSC	Canon RF-S 10-18mm f/4.5-6.3 IS STM	19596 CR1845-Z		37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	37129 N100 180mm Optical Glass Wideangle Dome Port							
						37305 N100 to N120 35.5mm Port Adaptor II <i>* This setup is only compatible with 37305 after SN:A544975, older version 37305 can be upgraded using lock mechanism 95851</i>	18802 8.5" Acrylic dome port					
							18809 180mm Optical Glass Wide Angle Port					
							18812 230mm Optical Glass Wide Angle Port II					
CANON EF-MOUNT	Canon EF-mount Lenses with Canon Mount Adaptor EF-EOS R <i>* Canon control ring and Drop-in filter mount adaptors are not supported by these setups</i>		37305 N100 to N120 35.5mm Port Adaptor II <i>* This setup is only compatible with 37305 after SN:A544975, older version 37305 can be upgraded using lock mechanism 95851</i>		N120 Canon EF-Mount Port System							
	Canon RF mount Fullframe Lenses		37305 N100 to N120 35.5mm Port Adaptor II <i>* This setup is only compatible with 37305 after SN:A544975, older version 37305 can be upgraded using lock mechanism 95851</i>		N120 Canon RF-Mount Port System							

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System

Last Updated : 2024-08-23

* This port chart is subject to updating as new information becomes available