



## N85 PORT SYSTEM FOR CANON EF-M-MOUNT CAMERA SYSTEM ( APS-C Format Lens )

	CAMERA LENS	GEAR	PORT ADAPTOR	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
MACRO APSC	Canon EF-S 60mm f/2.8 Macro USM with Canon EF-M Lens Adapter Kit	19521 C60-F	36184 N85 to N120 41.5mm Port Adaptor  <i>* This setup is only compatible with with 36184 after SN:A367377, older version 36184 can be upgraded using lock mechanism 95851</i>	18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81302 CMC - 2	Max. Magnification 1.6X Working Distance 38-120mm	
					SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1	Max. Magnification 1.6X Working Distance 28-94mm	
STANDARD ZOOM APSC	Canon EF-M 15-45mm f/3.5-6.3 IS STM	36195 CM1545-Z		36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 37-81mm	
					SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification 0.7X Working Distance 59-150mm	
	Canon EF-M 22mm f/2 STM			36126 E16 Mancake Port	83250 M67 to Bayonet Mount Converter II	* 83202 WWL - 1B	Lens FOV 74-33° Converted FOV 128-57° Zoom Range 18-45mm	
						83203 WWL - C	Lens FOV 76-33° Converted FOV 117-51° Zoom Range 17-45mm	
						83202 WWL - 1B	Lens FOV 63° Converted FOV 109°	
CANON EF-MOUNT	Canon EF 8-15mm f/4L Fisheye USM with Canon EF-M Lens Adapter Kit	19537 C815-Z	36184 N85 to N120 41.5mm Port Adaptor  <i>* This setup is only compatible with with 36184 after SN:A367377, older version 36184 can be upgraded using lock mechanism 95851</i>	22130 N120 Extension Ring 30 II	* 18811 140mm Optical Glass Fisheye Port with Removable Shade			
	Canon EF 100mm f/2.8L Macro IS USM with Canon EF-M Lens Adapter Kit	19523 C100IS-F	36204 N85 to N120 60mm Port Adaptor  <i>* This setup is only compatible with with 36204 after SN:A457812, older version 36204 can be upgraded using lock mechanism 95851</i>	22130 N120 Extension Ring 30 II	18704 Macro Port 41	SMC/CMC Option 1 - M67 Thread <b>81228</b> M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81201 SMC - 1	Max. Magnification 2.0X Working Distance 45-95mm
						SMC/CMC Option 2 - Bayonet Mount <b>83250 + 83214</b> M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81202 SMC - 2	Max. Magnification 3.4X Working Distance 23-39mm
			36184 N85 to N120 41.5mm Port Adaptor  <i>* This setup is only compatible with with 36184 after SN:A367377, older version 36184 can be upgraded using lock mechanism 95851</i>		18703 Macro Port 94	81302 CMC - 2	Max. Magnification 2.1X Working Distance 53-127mm	
	Other Canon EF-mount Lenses with Canon EF-M Lens Adapter Kit		36184 N85 to N120 41.5mm Port Adaptor  <i>* This setup is only compatible with with 36184 after SN:A367377, older version 36184 can be upgraded using lock mechanism 95851</i>		N120 Canon EF-Mount Port System			

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

\* Recommended Nauticam underwater optics based on best underwater optical performance

\* Recommended Port System

Last Updated : 2024-08-23

\* This port chart is subject to updating as new information becomes available