



N100 PORT SYSTEM FOR FUJIFILM X-MOUNT CAMERA SYSTEM (APS-C Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APS-C	Fujifilm XF 60mm f/2.4 R Macro			37401 / 37430 N100 Extension Ring 30 / N100 Extension Ring 30 II	37127 N100 Flat Port 32			
			36471 N100 to N85 Port Adaptor		36135 N85 Flat Port 45			
MACRO APS-C	Zeiss Touit 50mm f/2.8M			37401 / 37430 N100 Extension Ring 30 / N100 Extension Ring 30 II	37127 N100 Flat Port 32	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 1.3X Working Distance 17-75mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification 1.0X Working Distance 30-130mm
						83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL - 1	Lens FOV 31° Converted FOV 100°
STANDARD ZOOM APS-C	Fujifilm XC 15-45mm f/3.5-5.6 OIS PZ	36476 X1545PZ-Z			36478 N100 Flat Port 40	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83202 WWL - 1B	Lens FOV 75-35° Converted FOV 130-60° Zoom Range 18-45mm
							* 83203 WWL - C	Lens FOV 84-35° Converted FOV 130-54° Zoom Range 16-45mm
STANDARD ZOOM APS-C	Fujifilm XF 18-55mm f/2.8-4 R LM OIS	36474 X1855-Z		37401 / 37430 N100 Extension Ring 30 / N100 Extension Ring 30 II	* 85206 N120/N100 WACP - 1B			Lens FOV 75-52° Converted FOV 130-90° Zoom Range 18-30mm
					85203 N100 WACP-1			
STANDARD ZOOM APS-C				37403 / 37433 N100 Extension Ring 50 / N100 Extension Ring 50 II	* 37129 N100 180mm Optical Glass Wide Angle Port			
				37304 N100 to N120 55mm Port Adaptor <i>* This setup is only compatible with 37304 after SN:A411796, older version 37304 can be upgraded using lock mechanism 95851</i>	18809 180mm Optical Glass Wide Angle Port			
WIDE ANGLE APS-C	Fujifilm XF 8-16mm f/2.8 R LM WR	36477 X816-Z	37304 N100 to N120 55mm Port Adaptor <i>* This setup is only compatible with 37304 after SN:A411796, older version 37304 can be upgraded using lock mechanism 95851</i>	22130 N120 Extension Ring 30 II	* 18812 230mm Optical Glass Wide Angle Port II			
WIDE ANGLE APS-C	Fujifilm XF 16-50mm f/2.8-4.8 R LM WR	36480 XF1650-Z		37408 / 37431 N100 Extension Ring 35 / N100 Extension Ring 35 II	85205 N100 WACP - C			Lens FOV 76-32° Converted FOV 132-55° Zoom Range 18-50mm
					85206 N100/N120 WACP-1B			
WIDE ANGLE APS-C				37403/ 37433 N100 Extension Ring 50 / N100 Extension Ring 50 II	37129 N100 180mm Optical Glass Wide Angle Port			
				37304 N100 to N120 55mm Port Adaptor <i>* This setup is only compatible with 37304 after SN:A411796, older version 37304 can be upgraded using lock mechanism 95851</i>	18809 180mm Optical Glass Wide Angle Port			
WIDE ANGLE APS-C	Fujifilm XF 10-24mm f/4 R OIS	36475 X1024-Z		37403 / 37433 N100 Extension Ring 50 / N100 Extension Ring 50 II	* 37129 N100 180mm Optical Glass Wide Angle Port			
WIDE ANGLE APS-C	Fujifilm XF 10-24mm f/4 R OIS WR	36479 X1024WR-Z		37403 / 37433 N100 Extension Ring 50 / N100 Extension Ring 50 II	* 37129 N100 180mm Optical Glass Wide Angle Port			
WIDE ANGLE APS-C	Fujifilm XF 18mm f/2 R				36472 N100 Flat Port 13	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83202 WWL - 1B	Lens FOV 76.5° Converted FOV 132°
WIDE ANGLE APS-C	Fujifilm XF 23mm f/2 R				37127 N100 Flat Port 32	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83202 WWL - 1B	Lens FOV 63.4° Converted FOV 110°

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended Nauticam underwater optics based on best underwater optical performance

* Recommended Port System

Last Updated : 2024-08-23

* This port chart is subject to updating as new information becomes available