



COMPACT & N50 PORT SYSTEM FOR COMPACT CAMERA SYSTEM

CAMERA (HOUSING)	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE					
Sony Cyber-shot DSC-RX100 Mark V (17418/17418P) NA-RX100V / Pro Package * 24-70mm (35mm equivalent) * Port is inexchangeable for this housing		SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC-1	Smallest Subject Size Working Distance	35 x 23.3mm 55-75 mm				
		SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC-2	Smallest Subject Size Working Distance	48 x 32mm 80-124 mm				
		83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL - C	Lens FOV Converted FOV	84-34° 130-52°				
			83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-34° 130-58° 28-70 mm				
			86201 MWL-1	Lens FOV Converted FOV Zoom Range	37-34° 138-128° 65-70 mm				
		Sony Cyber-shot DSC-RX100 Mark VI (17421/17421P) NA-RX100VI / Pro Package * 24-200mm (35mm equivalent) * Port is exchangeable for this housing	38702 N50 3.5" Acrylic Wide Angle Dome Port	25107 M67 Flip Diopter Holder	81202 SMC-2	Smallest Subject Size Working Distance	7.5 x 5 mm 34-37 mm		
					81203 SMC-3	Smallest Subject Size Working Distance	16 x 10.7 mm 91-103 mm		
					83203 WWL - C	Lens FOV Converted FOV Zoom Range	84-46° 130-70° 24-50 mm		
					83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1	Smallest Subject Size Working Distance	38 x 25.3 mm 25-95 mm	
						81302 CMC-2	Smallest Subject Size Working Distance	48.5 x 32.3 mm 50-160 mm	
					86201 MWL-1	Lens FOV Converted FOV Zoom Range	40-37° 150-138° 60-65 mm		
						83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-37° 130-64° 28-65 mm	
83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1				Smallest Subject Size Working Distance	34 x 22.7 mm 40-85 mm			
	81302 CMC-2				Smallest Subject Size Working Distance	43.5 x 29 mm 58-154 mm			
Sony Cyber-shot DSC-RX100 Mark VII (17424/17424P) NA-RX100VII / Pro Package * 24-200mm (35mm equivalent) * Port is exchangeable for this housing	38702 N50 3.5" Acrylic Wide Angle Dome Port				25107 M67 Flip Diopter Holder	81202 SMC-2	Smallest Subject Size Working Distance	7.5 x 5 mm 34-37 mm	
						81203 SMC-3	Smallest Subject Size Working Distance	16 x 10.7 mm 91-103 mm	
						83203 WWL - C	Lens FOV Converted FOV Zoom Range	84-46° 130-70° 24-30 mm	
		86201 MWL-1	Lens FOV Converted FOV Zoom Range	37° 138° 65 mm					
			83202 WWL - 1B	Lens FOV Converted FOV Zoom Range		75-37° 130-64° 28-65 mm			
		83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1	Smallest Subject Size Working Distance		34 x 22.7 mm 40-85 mm			
			81302 CMC-2	Smallest Subject Size Working Distance		43.5 x 29 mm 58-154 mm			
		Canon Powershot G5XMKII (17331/17331P) NA-G5XII / Pro Package * 24-120mm (35mm equivalent) * Port is exchangeable for this housing	38702 N50 3.5" Acrylic Wide Angle Dome Port	25107 M67 Flip Diopter Holder		81301 CMC-1	Smallest Subject Size Working Distance	21 x 14 mm 44-72 mm	
						81302 CMC-2	Smallest Subject Size Working Distance	21x18mm 67-120mm	
						83203 WWL - C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm	
						83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-46° 130-80° 28-50mm	
						83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1	Smallest Subject Size Working Distance	40x26.7mm 20-72mm
	81302 CMC-2				Smallest Subject Size Working Distance	47x31.3mm 33-122mm			
Canon Powershot G7XMKII (17324 NA-G7XII) * 24-100mm (35mm equivalent) * Port is exchangeable for this housing	38702 N50 3.5" Acrylic Wide Angle Dome Port				SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC-1	Smallest Subject Size Working Distance	23x13.3mm 56-72mm	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC-2	Smallest Subject Size Working Distance	31x20.7mm 87-122mm
						83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL-1	Lens FOV Converted FOV Zoom Range	37-24° 138-90° 65-100mm
						83203 WWL - C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm	
							83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-37° 130-64° 28-65mm
						83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1	Smallest Subject Size Working Distance	23x13.3mm 45-72mm
			81302 CMC-2	Smallest Subject Size Working Distance		31x20.7mm 66-122mm			
		Canon Powershot G7XMKIII (17330P) NA-G7XIII Pro Package * 24-100mm (35mm equivalent) * Port is exchangeable for this housing	38702 N50 3.5" Acrylic Wide Angle Dome Port	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>		81301 CMC-1	Smallest Subject Size Working Distance	23x13.3mm 56-72mm	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC-2	Smallest Subject Size Working Distance	31x20.7mm 87-122mm
						83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL-1	Lens FOV Converted FOV Zoom Range	37-24° 138-90° 65-100mm
						83203 WWL - C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm	
							83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-37° 130-64° 28-65mm
83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1				Smallest Subject Size Working Distance	33x22mm 45-72mm			
	81302 CMC-2				Smallest Subject Size Working Distance	41x27.3mm 66-122mm			
Canon Powershot G7XMKIII (17330P) NA-G7XIII Pro Package * 24-100mm (35mm equivalent) * Port is exchangeable for this housing	38702 N50 3.5" Acrylic Wide Angle Dome Port				SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC-1	Smallest Subject Size Working Distance	23x13.3mm 56-72mm	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC-2	Smallest Subject Size Working Distance	31x20.7mm 87-122mm
						83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	86201 MWL-1	Lens FOV Converted FOV Zoom Range	37-24° 138-90° 65-100mm
						83203 WWL - C	Lens FOV Converted FOV Zoom Range	84-46° 130-71° 24-50mm	
							83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-37° 130-64° 28-65mm
		83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1	Smallest Subject Size Working Distance		33x22mm 45-72mm			
			81302 CMC-2	Smallest Subject Size Working Distance		41x27.3mm 66-122mm			
		Panasonic Lumix DC-LX100II (17717 NA-LX100II) * 24-75mm (35mm equivalent) * Port is exchangeable for this housing	38702 N50 3.5" Acrylic Wide Angle Dome Port	25107 M67 Flip Diopter Holder		81301 CMC-1	Smallest Subject Size Working Distance	33.5x22.3mm 50-77mm	
						81302 CMC-2	Smallest Subject Size Working Distance	47x31.3mm 76-130mm	
						83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-57° 130-99° 28-40mm	
						83203 WWL - C	Lens FOV Converted FOV Working Distance	84-72° 130-112° 24-30mm	
							83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	75-72° 130-125° 28-30mm
Panasonic Lumix DC-LX10 (LX15) (17714 NA-LX10) * 24-72mm (35mm equivalent) * Port is inexchangeable for this housing	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>				81301 CMC-1	Smallest Subject Size Working Distance	34x22.7mm 48-73mm		
					SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC-2	Smallest Subject Size Working Distance	46x30.7mm 76-128mm	
					83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL - C	Lens FOV Converted FOV Zoom Range	70-34° 108-53° 32-72mm	
						83202 WWL - 1B	Lens FOV Converted FOV Zoom Range	58-34° 108-60° 38-72mm	
						86201 MWL-1	Lens FOV Converted FOV Zoom Range	37-34° 138-128° 65-72mm	
					Olympus Tough TG5/TG6/TG7 (with M52 Thread) * 24-100mm (35mm equivalent) * Port is inexchangeable for this housing	38024 + 81228 M52 to M67 Step Up Adaptor Ring + M67 Spacer Ring for SMC/CMC <i>(81228 is included in all SMC/CMC)</i>	81301 CMC-1	Smallest Subject Size Working Distance	19x12.7mm 34-78mm
							SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC-2	Smallest Subject Size Working Distance
		83203 WWL - C	Lens FOV Converted FOV	84-24° 130-37°					
		83214 Bayonet Mount Adaptor for SMC/CMC	81301 CMC-1	Smallest Subject Size Working Distance			19x12.7mm 34-78mm		
			81302 CMC-2	Smallest Subject Size Working Distance			21x14mm 28.5-98mm		
		Olympus PT-058/PT-059 Underwater Housing	83256 Bayonet Mount Converter for Olympus PT-058/PT-059	83203 WWL - C			Lens FOV Converted FOV	84-24° 130-37°	

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System