

N85 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM

(APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANC	CE
MACRO APS-C	Sony E 30mm				36135 N85 Macro Port 45				
	f/3.5 Macro	36171			36128				
	L	SE30-F			N85 Macro Port 45 with Focus Knob				
	ZEISS Touit 50mm f/2.8M Macro			36630 N85 Extension Ring 30	36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC	81301 CMC - 1	Max. Magnification 1.3X Working Distance 17-75mm	n
						(included in all SMC/CMC packaging)			
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II +	81302 CMC-2	Max. Magnification 1.0X Working Distance 30-130mm	ım
						Bayonet Mount Adaptor for SMC/CMC 83250	86201	Lens FOV 31°	
						M67 to Bayonet Mount Converter II (included in all MWL-1 packaging)	MWL - 1	Converted FOV 116°	
MACRO FULL FRAME	0		04007		40704	20070 - 2004		Max. Magnification 1.4X	
	Sony FE 50mm f/2.8 Macro		36207 N85 to N120 50mm Port Adaptor II with Knob		18704 Macro Port 41	83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1	Working Distance 6-73mm	
			 This setup is only compatible wi with 36207 SN:A448780 onward version 36207 can be upgraded 				81302 CMC - 2	Max. Magnification 1.3X Working Distance 12-125mm	ım
	Sony FE 90mm		using lock mechanism 95851 36204		18701	SMC/CMC Option 1 - M67 Thread	81202	Max. Magnification 2.9X	
	f/2.8 Macro G OSS		N85 to N120 60mm Port Adaptor II * This setup is only compatible wi	th	Macro Port 60	81228 M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging)	SMC - 2	Working Distance 23-39mm	n
			with 36204 SN:A457812 onward version 36204 can be upgraded using lock mechanism 95851	s, older			81203 SMC - 3	Max. Magnification 2.1X Working Distance 47-101mi	nm
		36175	36205		37123	SMC/CMC Option 2 - Bayonet Mount	81501	Max. Magnification 1.1X	
	·	SFE90-F	N85 to N100 65mm Port Adaptor		N100 Macro Port 55 * This setup is only compatible with	83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	MFO-1	Working Distance 107-1082	2mm
					37123 SN:A175724 onwards				
STANDARD ZOOM APSC	Sony E PZ 16-50mm	36172			36228	SMC/CMC Option 1 - M67 Thread	81301 CMC - 1	Max. Magnification 0.9X	
	f/3.5-5.6 OSS	SE1650-PZ			N85 Macro Port 40 with Knob	81228 M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging)	CIVIC - 1	Working Distance 46-74mm	n
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214	81302 CMC-2	Max. Magnification 0.7X Working Distance 69-121mi	am
						M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC			
						83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV 80-31° Converted FOV 124-48° Zoom Range 17-50mm	
							* 83202 WWL - 1B	Lens FOV 75-31° Converted FOV 130-54°	
							WILL 15	Zoom Range 19-50mm	
	Sony Vario-Tessar T* E 16-70mm f/4 ZA OSS	36174 SE1670-Z			36129 7" Acrylic Dome Port				
			36207 N85 to N120 50mm Port Adaptor II	22120 N120 Extension Ring 20 II	* 18809 180mm Optical Glass Wide A	ngle Port			
			with Knob * This setup is only compatible with 36207		18705 Macro Port 45	83250 M67 to Bayonet Mount Converter II	86201 MWL - 1	Lens FOV 83-23° Converted FOV 100-82°	
			SN:A448780 onwards, older version 36207 can be upgraded using lock mechanism 95851			(included in all MWL-1 packaging)		Zoom Range 50-60mm	n
WIDE ANGLE APS-C	Sony E 10-18mm f/4 OSS	36173 SE1018-Z			36129 7" Acrylic Dome Port				
			36204 N85 to N120		* 18809 180mm Optical Glass Wide A	ngle Port			
			60mm Port Adaptor * This setup is only compatible wi with 36204 SN:A457812 onward version 36204 can be upgraded						
			using lock mechanism 95851						
			36207 N85 to N120 50mm Port Adaptor II with Knob		18809 180mm Optical Glass Wide A	ngle Port			
			* This setup is only compatible wi with 36207 SN:A448780 onward version 36207 can be upgraded						
	Sony E 10-20mm	36176	using lock mechanism 95851		36133				
	f/4 PZ G	SE1020-Z			6" Acrylic Dome Port				
			36207 N85 to N120 50mm Port Adaptor II with Knob		18809 180mm Optical Glass Wide Ai * this setup is only compatib 18809 SN:A561555 onwards	le with			
			* This setup is only compatible wi with 36207 SN:A448780 onward version 36207 can be upgraded		10005 01.A001000 0111414.				
	Sony E 16mm		using lock mechanism 95851		36126				
	f/2.8				E16 Pancake Port				
					* 36125 4.33" Acrylic Wide-angle Dom	ie Port			
	Sony E 16mm f/2.8 with Sony Fisheye Converter VCL-ECF1 / VCL-ECU1				36125 4.33" Acrylic Wide-angle Dom	ie Port			
	ZEISS Touit 12mm		36204						
	f/2.8		N85 to N120 60mm Port Adaptor * This setup is only compatible wi with 36204 SN:A457812 onward		18809 180mm Optical Glass Wide Angle Port				
			version 36204 can be upgraded using lock mechanism 95851						
			36207 N85 to N120 50mm Port Adaptor II						
			with Knob * This setup is only compatible wi with 36207 SN:A448780 onward						
			version 36207 can be upgraded using lock mechanism 95851						
	Sigma 19mm f/2.8 DN Art				36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II	83202 WWL - 1B	Lens FOV 73.5° Converted FOV 127°	

 $Max.\ Magnification\ is\ the\ maximum\ ratio\ that\ a\ subject\ can\ be\ reproduced\ on\ a\ camera's\ image\ sensor\ (APS-C-22.3\ x\ 15mm,\ Full\ Frame-36\ x\ 24mm)\ at\ the\ closest\ working\ distance.$

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System