

## N100 PORT SYSTEM FOR Canon RF-S CAMERA SYSTEM

(RF-S & EF-Mount Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANC	E
STANDARD ZOOM  APSC	Canon RF-S 18-45mm f4.5-6.3 IS STM	<b>19596</b> CR1845-Z			<b>37181</b> N100 Flat Port 50	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging)	81301 CMC-1	Max. Magnification Working Distance	
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81302 CMC - 2	Max. Magnification Working Distance	0.6X 68-140mm
						<b>83250</b> M67 to Bayonet Mount Converter II (included in all MWL-1 packaging)	* 83202 WWL-1B	Lens FOV Converted FOV Zoom Range	75-35° 130-60° 18-45mm
							83203 WWL-C	Lens FOV Converted FOV Zoom Range	75-35° 116-52° 18-45mm
							86201 MWL - 1	Lens FOV Converted FOV Zoom Range	40-35° 150-130° 38-45mm
				<b>37402 / 37432</b> N100 Extension Ring 40 / N100 Extension Ring 40 II	* 85206 N120/N100 WACP-1B				
					85203 N100 WACP-1			Lens FOV Converted FOV	75-35° 130-60°
			37305		85205 N100 WACP - C				
			N100 to N120 35.5mm Port Adaptor II * This setup is only compatible with 37305 SN:A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851		N120/N100 WACP-1B				
				37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	<b>85207</b> N120/N100 FCP-1			Lens FOV Converted FOV	74-34° 170-62°
WIDE ANGLE APS-C	Canon RF-S 10-18mm f/4.5-6.3 IS STM	<b>19596</b> CR1845-Z		37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	<b>37129</b> N100 180mm Optical Glass	s Wideangle Dome Port			
			37305 N100 to N120 35.5mm Port Adaptor II * This setup is only compatible with 37305		<b>18802</b> 8.5* Acrylic dome port				
			SN:A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851		180mm Optical Glass Wide An  18812 230mm Optical Glass Wide An	-			
CANON EF-MOUNT	* Canon control ring and Drop-in filter mount 37305 SN:A544975 o adaptors are not supported by these setups version 37305 can be		N100 to N120	N120 Canon EF-Mount Port System					
			35.5mm Port Adaptor II  * This setup is only compatible with 37305 SN:A544975 onwards, olde version 37305 can be upgraded using lock mechanism 95851						
	Canon RF mount Fullframe Lenses		37305 N100 to N120 35.5mm Port Adaptor II * This setup is only compatible with 37305 SN:A544975 onwards, olde version 37305 can be upgraded using lock mechanism 95851		N120 Canon RF-Mount Port System				

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- \* Recommended Nauticam underwater optics based on best underwater optical performance
- \* Recommended Port System