

## N100 PORT SYSTEM FOR NIKON Z-MOUNT CAMERA SYSTEM

(DX & F-Mount Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
MACRO DX	NIKKOR Z MC 50mm f/2.8 Macro			<b>37430</b> N100 Extension Ring 30 II	37601	83250 M67 to Bayonet Mount Converter II (included in all MWL-1 packaging)  83251 M77 to Bayonet Mount Converter II	<b>86201</b> MWL - 1	Lens FOV Converted FOV	31.5° 119°
STANDARD ZOOM DX	NIKKOR Z DX 16-50mm f/3.5-6.3 VR	<b>37602</b> Z1650PZ-Z			37601 N100 Flat Port 29	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging)  SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC  83250 M67 to Bayonet Mount Converter II	* 83203 WWL-C	Max. Magnification Working Distance  Max. Magnification Working Distance  Lens FOV Converted FOV Lens FOV Converted FOV Zoom Range	0.9X 45.5-75mm 0.67X 70-130mm 84-31.5° 130-49° 72-31.5° 125-55° 20-50mm
NIKON F-MOUNT	Nikon F-mount Lenses with Nikon Adaptor FTZ II  ** Trull AF/AE supported only when using FX or DX AF-S type G/D/E, AF-P type G/E, AF-I type D lenses and AF-S/AF-I Teleconverters.		37305 N100 to N120 35.5mm Port Adaptor II * Nikon Adaptor FTZ old ver is only compatible with 75 before SN:A566710 * It is required to replace trip cover of Nikon adaptor FTZ #25220 Tripod socket repl * This setup is only compati 37305 SN:A544975 onwa version 37305 can be upgr using lock mechanism 958	oot socket z by acement ble with rds, older aded	N120 Nikon F-Mount Port System				

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- \* Recommended Nauticam underwater optics based on best underwater optical performance
- \* Recommended Port System