



## N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2

### FOR FULL FRAME 14MM EQUIVALENT LENSES TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	PORT ADAPTOR / EXTENSION RING	EXTENSION RING / PORT CONVERTER	PORT	OPTICAL PERFORMANCE
STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f2L USM	16343 RC2870F2 RC2870F3		22140 N120 Extension Ring 40 II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 SN:AS26311 onwards</small>	On Full Frame Sensor Lens FOV 75-63° Zoomed FOV 85-72° Zoom Range 28-35mm
	Canon EF-S 10-18mm f4.5-5.6 IS STM	16340 RC1018 Gear Set		21110 N120 Extension Ring 10	85204 N120 WACP-2	On APS-C Sensor Lens FOV 108-75° Zoomed FOV 128-85°
	Canon EF-S 10-22mm f3.5-4.5 IS USM	16303 + 16304 RC1022-Z + RC1022-F		21110 N120 Extension Ring 10 II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	On APS-C Sensor Lens FOV 108-63° Zoomed FOV 128-72°
WIDE ANGLE APS-C	Tokina AT-X 11-20mm f2.8 PRO DX	16328 RTC1120 Gear Set		22120 N120 Extension Ring 20 II	85204 N120 WACP-2	On APS-C Sensor Lens FOV 108-63° Zoomed FOV 128-72°
	Canon RF 14-35mm f4L IS USM	16342 CR1435 Gear Set		22110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	On Full Frame Sensor Lens FOV 114-63° Zoomed FOV 140-72°
	Canon RF 15-35mm f2.8L IS USM	16341 CR1535 Gear Set		22130 N120 Extension Ring 30 II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	On APS-C Sensor Lens FOV 89-42° Zoomed FOV 104-48°
WIDE ANGLE FULL FRAME	Canon RF 15-35mm f2.8L IS USM	16341 CR1535 Gear Set		22135 N120 Extension Ring 35 II	85204 N120 WACP-2	On Full Frame Sensor Lens FOV 114-63° Zoomed FOV 140-72°
	Canon RF 15-30mm f4.5-6.3 IS STM	16345 CR1530 Gear Set		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	On APS-C Sensor Lens FOV 84-44° Zoomed FOV 98-48°
	Canon EF 16-35mm f2.8 III USM	16311 + 16312 RC1635II-Z + RC1635II-F		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	On Full Frame Sensor Lens FOV 110-63° Zoomed FOV 133-72°
WIDE ANGLE FULL FRAME	Canon EF 16-35mm f2.8 III USM	16325 RC1635III Gear Set		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	On APS-C Sensor Lens FOV 84-44° Zoomed FOV 98-51°
	Canon EF 16-35mm f2.8 III USM	16325 RC1635III Gear Set		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	On Full Frame Sensor Lens FOV 107-63° Zoomed FOV 128-72°
	Canon EF 16-35mm f2.8 III USM	16325 RC1635III Gear Set		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	On APS-C Sensor Lens FOV 84-44° Zoomed FOV 98-51°
N120 NIKON F-MOUNT	Nikon AF-S NIKKOR 16-35mm f4G ED VR	19138 N1635-Z		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	Lens FOV 105-63° Zoomed FOV 128-72°
	Nikon AF-S 17-35mm f2.8D IF-ED	19130 N1735-Z		22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 104-63° Zoomed FOV 123-72°
STANDARD ZOOM FX	Nikkor Z 24-70mm f2.8 S Lens	19157 NZ2470F2.8S-Z		22125 N120 Extension Ring 25 II	85204 N120 WACP-2	Lens FOV 84-46° Zoomed FOV 98-56°
	Nikkor Z 14-24mm f2.8 S	19160 (V1) / 19202 (V2) NZ1424-Z (V1) / Z1424-Z (V2)		21110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	Lens FOV 114-87° Zoomed FOV 140-98°
WIDE ANGLE FX	Nikkor Z 14-30mm f4 S	19156 (V1) / 19203 (V2) NZ1430-Z (V1) / Z1430-Z (V2)		21110 N120 Extension Ring 10 II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 SN:AS26311 onwards</small>	Lens FOV 114-72° Zoomed FOV 140-81°
	Nikkor Z 14-24mm f2.8 S	19160 (V1) NZ1424-Z (V1)	22225 N120 FTZ Adaptor ER 25 with Knob	21110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	Lens FOV 114-87° Zoomed FOV 140-98°
WIDE ANGLE FX	Nikkor Z 14-30mm f4 S	19156 (V1) NZ1430-Z (V1)	22225 N120 FTZ Adaptor ER 25 with Knob	21110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 SN:AS26311 onwards</small>	Lens FOV 114-72° Zoomed FOV 140-81°
	Nikkor Z 14-30mm f4 S	19203 (V2) Z1430-Z (V2)	22125 N120 Extension Ring 25 II	21110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 SN:AS26311 onwards</small>	Lens FOV 114-72° Zoomed FOV 140-81°
WIDE ANGLE APS-C	Canon EF-S 10-18mm f4.5-5.6 IS STM	19549 C1018-Z		21110 N120 Extension Ring 10	85204 N120 WACP-2	Lens FOV 108-75° Zoomed FOV 128-85°
	Canon EF-S 10-22mm f3.5-4.5 IS STM	19525 C1022-Z		21110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	Lens FOV 108-63° Zoomed FOV 128-72°
	Tokina AT-X 116 PRO DX AF 11-16mm f2.8	19530 TC1116-Z		21110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	Lens FOV 110-81° Zoomed FOV 133-92°
WIDE ANGLE FULL FRAME	Canon EF 16-35mm f2.8 II USM	19527 C1635II-Z		22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 107-63° Zoomed FOV 128-72°
	Canon EF 16-35mm f2.8 III USM	19554 C1635III-Z		22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 107-63° Zoomed FOV 128-72°
	Canon EF 16-35mm f4 IS USM	19548 C1635F4-Z		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	Lens FOV 108-63° Zoomed FOV 128-72°
STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f2L USM	19595 CR2870-Z		22140 N120 Extension Ring 40 II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 SN:AS26311 onwards</small>	Lens FOV 75-63° Zoomed FOV 85-72° Zoom Range 28-35mm
	Canon RF 14-35mm f4L IS USM	19574 CR1435-Z		22110 N120 Extension Ring 10	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	Lens FOV 114-63° Zoomed FOV 140-72°
	Canon RF 15-30mm f4.5-6.3 IS STM	19597 CR1530-Z		22110 N120 Extension Ring 10 II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 SN:AS26311 onwards</small>	Lens FOV 114-63° Zoomed FOV 140-72°
WIDE ANGLE FULL FRAME	Canon RF 15-30mm f4.5-6.3 IS STM	19597 CR1530-Z		22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 110-71° Zoomed FOV 133-81°
	Canon RF 15-35mm f2.8L IS USM	19569 CR1535-Z		22135 N120 Extension Ring 35 II	85204 N120 WACP-2	Lens FOV 110-63° Zoomed FOV 133-72°
	Canon RF 15-35mm f2.8L IS USM	19569 CR1535-Z		22135 N120 Extension Ring 35 II	85204 N120 WACP-2	Lens FOV 110-63° Zoomed FOV 133-72°
WIDE ANGLE FULL FRAME	Panasonic Lumix S PRO 16-35mm f4	19728 PL1635-Z		22150 N120 Extension Ring 50 II	85204 N120 WACP-2	Lens FOV 105-63° Zoomed FOV 128-72°
	Sigma 14-24mm f2.8 DG DN Art	19726 SLE1424-Z		22125 N120 Extension Ring 25 II	85204 N120 WACP-2	Lens FOV 105-63° Zoomed FOV 128-72° Zoom Range 20-24mm
MACRO MEDIUM FORMAT	Lowa 17mm f4 GFx Zero-D	19824 + 19825 GL17-A + GL17-F		22135 + 22151 N120 Extension Ring 35 II + Focus Knob	85204 N120 WACP-2	Lens FOV 114° Zoomed FOV 140°
	Fujifilm GF 20-35mm F4 R WR	19827 GF2035-Z		22135 N120 Extension Ring 35 II	85204 N120 WACP-2	Lens FOV 108-76° Zoomed FOV 132-93°
	Fujifilm GF 23mm F4 R LM WR			22120 N120 Extension Ring 20 II	85204 N120 WACP-2	Lens FOV 100° Zoomed FOV 118°
CANON EF-MOUNT	Canon EF 16-35mm f2.8 III USM with Metabones EF-GFX mount Smart Expander 1.26x	TBD CDF1635III-Z		22180 N120 Extension Ring 80 II	85204 N120 WACP-2	Lens FOV 107-63° Zoomed FOV 128-72°
	Canon EF 16-35mm f4 IS USM with Metabones EF-GFX mount Smart Expander 1.26x	TBD CDF1635F4-Z		22160 N120 Extension Ring 60 II	85204 N120 WACP-2	Lens FOV 107-63° Zoomed FOV 128-72°
STANDARD ZOOM FULL FRAME	Sony FE 20-70mm f4 G	37174 SFE2070-Z		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2 <small>* slight vignetting at 20mm in RAW format</small>	Lens FOV 94-59° Zoomed FOV 116-73° Zoom Range 20-38mm
	Sony SEL2470GM FE 24-70mm f2.8 GM	37151 SFE2470GM-Z		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 84-34° Zoomed FOV 98-72° Zoom Range 24-35mm
	Sony SEL2470GM FE 24-70mm f2.8 GM	37151 + 37152 SFE2470GM-Z + SFE2470GM-F		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 84-34° Zoomed FOV 98-72° Zoom Range 24-35mm
WIDE ANGLE FULL FRAME	Sigma 24-70mm f2.8 DG DN Art	37171 SFP2470-Z		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 84-64° Zoomed FOV 98-74° Zoom Range 24-44mm
	Sony FE 14mm f1.8 GM			37306 N100 to N120 25mm Port Adaptor	85204 N120 WACP-2	Lens FOV 114° Zoomed FOV 140°
	Sony SEL1635GM FE 16-35mm f2.8 GM	37155 SFE1635GM-Z		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 107-63° Zoomed FOV 128-77°
WIDE ANGLE FULL FRAME	Sony SEL1635GM2 FE 16-35mm f2.8 GM II	37175 SFE1635GMII-Z		37306 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	Lens FOV 107-63° Zoomed FOV 128-77°
	Sony SEL1635Z Vario-Tessar* FE 16-35mm f4 ZA OSS	37175 + 37176 SFE1635GMII-Z + SFE1635GMII-F		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 SN:AS26311 onwards</small>	Lens FOV 107-63° Zoomed FOV 128-77°
	Sony SEL1635Z Vario-Tessar* FE 16-35mm f4 ZA OSS	37145 + 37146 SE1635-Z + SE1635-F		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2 <small>* This setup is only compatible with WACP-2 before SN:AS26311</small>	Lens FOV 107-63° Zoomed FOV 128-77°
WIDE ANGLE FULL FRAME	Sony FE PZ 16-35mm f4 G	37172 SFE1635-Z		37306 N100 to N120 25mm Port Adaptor	85204 N120 WACP-2	Lens FOV 107-63° Zoomed FOV 128-77°
	Sony FE 24mm f1.4 GM			37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 84° Zoomed FOV 98°
	Sigma 14-24mm f2.8 DG DN	19726 SLE1424-Z		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 94-84° Zoomed FOV 115-98° Zoom Range 20-24mm

#### 85204 N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 (WACP-2) For Full Frame 14mm Equivalent Lenses to 140° Full Zoom-through

<b>Specifications</b>		<b>Package includes</b>
Dimension (mm)	: DIA 297 x H 220 (from port mount to front lens element)	• WACP-2
Weight in Air	: 7.35 kg	• Front hard lens cap
Buoyancy in Water	: Negative 0.27 kg	• Rear lens caps
Body Construction	: Hard-anodized aluminum alloy	• Padded carrying bag
Lens Construction	: 4 Elements	• 90140 N120 Port O-ring
Lens Coating	: Anti-corrosion coating outside of dome	• Cleaning Cloth
Focus Distance	: From front element of lens to infinity	• Lubricant
Maximum FOV (underwater)	: 140° (Ref. 28mm equivalent)	
Lens Mount	: N120 Port Mount	
Depth Rating	: 100m	
Pre-installed	: Integrated aluminium float collar	