COMPACT & N50 PORT SYSTEM FOR COMPACT CAMERA SYSTEM

	CAMERA (HOUSING)	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
SONY	**Sony Cyber-shot DSC-RX100 Mark V (17418/17418P NA-RX100V / Pro Package)** * 24-70mm (35mm equivalent) *Port is inexchangable for this housing*		SMC/CMC Option 1 - M67 Thread **81228** M67 Spacer Ring for SMC/CMC *(included in all SMC/CMC packaging)*	**81301** CMC - 1	Smallest Subject Size / Working Distance **35 x 23.3 mm** / **55-75 mm**
			SMC/CMC Option 2 - Bayonet Mount **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	**81302** CMC - 2	Smallest Subject Size / Working Distance **48 x 32mm** / **80-124 mm**
			83250 M67 to Bayonet Mount Converter II *(included in all MWL-1 packaging)*	**83203** WWL - C	Lens FOV / Converted FOV **84-34°** / **130-52°**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-34°** / **130-58°** / **28-70 mm**
				86201 MWL - 1	Lens FOV / Converted FOV / Zoom Range **37-34°** / **138-128°** / **65-70 mm**
	Sony Cyber-shot DSC-RX100 Mark VI (17421/17421P NA-RX100VI / Pro Package) * 24-200mm (35mm equivalent) *Port is exchangable for this housing*	**38702** N50 3.5° Acrylic Wide Angle Dome Port			
			25107 M67 Flip Diopter Holder	**81201** SMC - 1	Smallest Subject Size / Working Distance **14 x 9.3 mm** / **84-94 mm**
				81202 SMC - 2	Smallest Subject Size / Working Distance **7.5 x 5 mm** / **34-37 mm**
		38704 N50 Short Port 22 with Bayonet Mount * change part from housing		**83203** WWL - C	Lens FOV / Converted FOV / Zoom Range **84-46°** / **130-70°** / **24-50 mm**
			83214 Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **38 x 25.3 mm** / **25-95 mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **48.5 x 32.3 mm** / **50-160 mm**
		38703 N50 Short Port 25 with Bayonet Mount * change part from housing		**86201** MWL - 1	Lens FOV / Converted FOV / Zoom Range **40-37°** / **150-138°** / **60-65 mm**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-37°** / **130-64°** / **28-65 mm**
			83214 Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **34 x 22.7 mm** / **40-85 mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **43.5 x 29 mm** / **58-154 mm**
	Sony Cyber-shot DSC-RX100 Mark VII (17424/17424P NA-RX100VII / Pro Package) * 24-200mm (35mm equivalent) *Port is exchangable for this housing*	**38702** N50 3.5° Acrylic Wide Angle Dome Port			
			25107 M67 Flip Diopter Holder	**81201** SMC - 1	Smallest Subject Size / Working Distance **14 x 9.3 mm** / **84-94 mm**
				81202 SMC - 2	Smallest Subject Size / Working Distance **7.5 x 5 mm** / **34-37 mm**
		38705 N50 Short Port 17 with Bayonet Mount * change part from housing		**83203** WWL - C	Lens FOV / Converted FOV / Zoom Range **84-46°** / **130-70°** / **24-30 mm**
		38703 N50 Short Port 25 with Bayonet Mount * change part from housing		**86201** MWL - 1	Lens FOV / Converted FOV / Zoom Range **37°** / **138°** / **65 mm**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-37°** / **130-64°** / **28-65 mm**
			83214 Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **34 x 22.7 mm** / **40-85 mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **43.5 x 29 mm** / **58-154 mm**
CANON	**Canon Powershot G5XMKII (17331/17331P NA-G5XII / Pro Package)** * 24-120mm (35mm equivalent) *Port is exchangable for this housing*	**38702** N50 3.5° Acrylic Wide Angle Dome Port			
			25107 M67 Flip Diopter Holder	**81301** CMC - 1	Smallest Subject Size / Working Distance **21 x 14 mm** / **44-72 mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **21x18mm** / **67-120mm**
				81201 SMC - 1	Smallest Subject Size / Working Distance **24x16mm** / **58-93mm**
		38703 N50 Short Port 25 with Bayonet Mount * change part from housing		**83203** WWL - C	Lens FOV / Converted FOV / Zoom Range **84-46°** / **130-71°** / **24-50mm**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-46°** / **130-80°** / **28-50mm**
			83214 Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **40x26.7mm** / **20-72mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **47x31.3mm** / **33-122mm**
	Canon Powershot G7XMKII (17324 NA-G7XII) * 24-100mm (35mm equivalent) *Port is exchangable for this housing*	**38702** N50 3.5° Acrylic Wide Angle Dome Port			
			SMC/CMC Option 1 - M67 Thread **81228** M67 Spacer Ring for SMC/CMC *(included in all SMC/CMC packaging)*	**81301** CMC - 1	Smallest Subject Size / Working Distance **23x13.3mm** / **56-72mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **31x20.7mm** / **87-122mm**
			SMC/CMC Option 2 - Bayonet Mount **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	**81201** SMC - 1	Max. Magnification / Working Distance **25.5x17mm** / **73-93mm**
			83250 M67 to Bayonet Mount Converter II *(included in all MWL-1 packaging)*	**86201** MWL - 1	Lens FOV / Converted FOV / Zoom Range **37-24°** / **138-90°** / **65-100mm**
		38703 N50 Short Port 25 with Bayonet Mount * change part from housing		**83203** WWL - C	Lens FOV / Converted FOV / Zoom Range **84-46°** / **130-71°** / **24-50mm**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-37°** / **130-64°** / **28-65mm**
			83214 Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **23x13.3mm** / **45-72mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **31x20.7mm** / **66-122mm**
	Canon Powershot G7XMKIII (17330/17330P NA-G7XIII / Pro Package) * 24-100mm (35mm equivalent) *Port is exchangable for this housing*	**38702** N50 3.5° Acrylic Wide Angle Dome Port			
			SMC/CMC Option 1 - M67 Thread **81228** M67 Spacer Ring for SMC/CMC *(included in all SMC/CMC packaging)*	**81301** CMC - 1	Smallest Subject Size / Working Distance **23x13.3mm** / **56-72mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **31x20.7mm** / **87-122mm**
			SMC/CMC Option 2 - Bayonet Mount **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	**81201** SMC - 1	Max. Magnification / Working Distance **25.5x17mm** / **73-93mm**
			83250 M67 to Bayonet Mount Converter II *(included in all MWL-1 packaging)*	**86201** MWL - 1	Lens FOV / Converted FOV / Zoom Range **37-24°** / **138-90°** / **65-100mm**
		38703 N50 Short Port 25 with Bayonet Mount * change part from housing		**83202** WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-37°** / **130-64°** / **28-65mm**
				86201 MWL - 1	Lens FOV / Converted FOV / Zoom Range **37-34°** / **138-128°** / **65mm**
			83214 Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **33x22mm** / **45-72mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **41x27.3mm** / **66-122mm**
		38704 N50 Short Port 22 with Bayonet Mount * change part from housing		**83203** WWL - C	Lens FOV / Converted FOV / Working Distance **84-46°** / **130-71°** / **24-50mm**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-46°** / **130-80°** / **28-50mm**
			83214 Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **33x22mm** / **45-72mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **41x27.3mm** / **66-122mm**
PANASONIC	**Panasonic Lumix DC-LX100II (17717 NA-LX100II)** * 24-75mm (35mm equivalent) *Port is exchangable for this housing*	**38702** N50 3.5° Acrylic Wide Angle Dome Port			
			25107 M67 Flip Diopter Holder	**81301** CMC - 1	Smallest Subject Size / Working Distance **33.5x22.3mm** / **50-77mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **47x31.3mm** / **76-130mm**
		38703 N50 Short Port 25 with Bayonet Mount * change part from housing		**83202** WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-57°** / **130-99°** / **28-40mm**
		38704 N50 Short Port 22 with Bayonet Mount * change part from housing		**83203** WWL - C	Lens FOV / Converted FOV / Working Distance **84-72°** / **130-112°** / **24-30mm**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **75-72°** / **130-125°** / **28-30mm**
	Panasonic Lumix DC-LX10 (LX15) (17714 NA-LX10) * 24-72mm (35mm equivalent) *Port is inexchangable for this housing*		SMC/CMC Option 1 - M67 Thread **81228** M67 Spacer Ring for SMC/CMC *(included in all SMC/CMC packaging)*	**81301** CMC - 1	Smallest Subject Size / Working Distance **34x22.7mm** / **48-73mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **46x30.7mm** / **76-128mm**
			SMC/CMC Option 2 - Bayonet Mount **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **34x22.7mm** / **48-73mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **46x30.7mm** / **76-128mm**
			83250 M67 to Bayonet Mount Converter II *(included in all MWL-1 packaging)*	**83203** WWL - C	Lens FOV / Converted FOV / Zoom Range **70-34°** / **108-53°** / **32-72mm**
				83202 WWL - 1B	Lens FOV / Converted FOV / Zoom Range **58-34°** / **100-53°** / **38-72mm**
				86201 MWL - 1	Lens FOV / Converted FOV / Zoom Range **37-34°** / **138-128°** / **65-72mm**
OLYMPUS	**Olympus Tough TG5/TG6/TG7 (with M52 Thread)** * 24-100mm (35mm equivalent) *Port is inexchangable for this housing*		**83255** M52 to Bayonet Mount Converter	**83203** WWL - C	Lens FOV / Converted FOV **84-24°** / **130-37°**
			SMC/CMC Option 1 - M67 Thread **38024 + 81228** M52 to M67 Step Up Adaptor Ring + M67 Spacer Ring for SMC/CMC *(81228 is included in all SMC/CMC*	**81301** CMC - 1	Smallest Subject Size / Working Distance **19x12.7mm** / **34-78mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **21x14mm** / **28.5-98mm**
			SMC/CMC Option 2 - Bayonet Mount **83250 + 83214** M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	**81301** CMC - 1	Smallest Subject Size / Working Distance **19x12.7mm** / **34-78mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **21x14mm** / **28.5-98mm**
	Olympus Tough TG5/TG6/TG7 (with Bayonet Mount) * 24-100mm (35mm equivalent) *Port is inexchangable for this housing*		**83214** Bayonet Mount Adaptor for SMC/CMC	**83203** WWL - C	Lens FOV / Converted FOV **84-24°** / **130-37°**
				81301 CMC - 1	Smallest Subject Size / Working Distance **19x12.7mm** / **34-78mm**
				81302 CMC - 2	Smallest Subject Size / Working Distance **21x14mm** / **28.5-98mm**
OLYMPUS	**Olympus PT-058/ PT-059 Underwater Housing**		**83256** Bayonet Mount Converter for Olympus PT-058/PT-059	**83203** WWL - C	Lens FOV / Converted FOV **84-24°** / **130-37°**

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended Nauticam underwater optics based on best underwater optical performance

★ Recommended Port System