



N85 PORT SYSTEM FOR SONY E-MOUNT CAMERA SYSTEM (APS-C & Full Frame Format Lens)

	CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APSC	Sony E 30mm f/3.5 Macro		36171 SE30-F		36135 N85 Macro Port 45 36128 N85 Macro Port 45 with Focus Knob			
	ZEISS Touit 50mm f/2.8M Macro			36630 N85 Extension Ring 30	36135 N85 Macro Port 45	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging) SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC 83250 M67 to Bayonet Mount Converter II (included in all MWL-1 packaging)	81301 CMC - 1 81302 CMC - 2 86201 MWL - 1	Max. Magnification 1.3X Working Distance 17-75mm Max. Magnification 1.0X Working Distance 30-130mm Lens FOV 31° Converted FOV 116°
MACRO FULL FRAME	Sony FE 50mm f/2.8 Macro			36207 N85 to N120 50mm Port Adaptor II with Knob	18704 Macro Port 41	83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81301 CMC - 1 81302 CMC - 2	Max. Magnification 1.4X Working Distance 6-73mm Max. Magnification 1.3X Working Distance 12-125mm
	Sony FE 90mm f/2.8 Macro G OSS		36175 SFE90-F	36204 N85 to N120 60mm Port Adaptor II 36205 N85 to N100 65mm Port Adaptor	18701 Macro Port 60 37123 N100 Macro Port 55 <i>* this setup is only compatible with 37123 after SN:A175724 09/2016</i>	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging) SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81201 SMC - 1 81202 SMC - 2	Max. Magnification 2.1X Working Distance 45-93mm Max. Magnification 2.9X Working Distance 23-39mm
STANDARD ZOOM APSC	Sony E PZ 16-50mm f/3.5-5.6 OSS		36172 SE1650-PZ		36228 N85 Macro Port 40 with Knob	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC (included in all SMC/CMC packaging) SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC 83250 M67 to Bayonet Mount Converter II	81301 CMC - 1 81302 CMC - 2 83203 WWL - C * 83202 WWL - 1B	Max. Magnification 0.9X Working Distance 46-74mm Max. Magnification 0.7X Working Distance 69-121mm Lens FOV 80-31° Converted FOV 124-48° Zoom Range 17-50mm Lens FOV 75-31° Converted FOV 130-54° Zoom Range 19-50mm
	Sony Vario-Tessar T* E 16-70mm f/4 ZA OSS		36174 SE1670-Z	36207 N85 to N120 50mm Port Adaptor II with Knob	36129 7" Acrylic Dome Port * 18809 180mm Optical Glass Wide Angle Port	83250 M67 to Bayonet Mount Converter II (included in all MWL-1 packaging)	86201 MWL - 1	Lens FOV 83-23° Converted FOV 100-82° Zoom Range 50-60mm
	Sony E 18-55mm f/3.5-5.6 OSS		36122 SE1855-PZ		36137 4" Wide Angle Port			
WIDE ANGLE APSC	Sony E 10-18mm f/4 OSS		36173 SE1018-Z	36204 N85 to N120 60mm Port Adaptor 36207 N85 to N120 50mm Port Adaptor II with Knob	36129 7" Acrylic Dome Port * 18809 180mm Optical Glass Wide Angle Port 18809 180mm Optical Glass Wide Angle Port			
	Sony E 10-20mm f/4 PZ G		36176 SE1020-Z	36207 N85 to N120 50mm Port Adaptor II with Knob	36133 6" Acrylic Dome Port 18809 180mm Optical Glass Wide Angle Port <i>* this setup is only compatible with 18809 after SN:A561555</i>			
	Sony E 16mm f/2.8				36126 E16 Pancake Port * 36125 4.33" Acrylic Wide-angle Dome Port			
	Sony E 16mm f/2.8 with Sony Fisheye Converter VCL-ECF1 / VCL-ECU1				36125 4.33" Acrylic Wide-angle Dome Port			
	ZEISS Touit 12mm f/2.8			36204 N85 to N120 60mm Port Adaptor 36207 N85 to N120 50mm Port Adaptor II with Knob	18809 180mm Optical Glass Wide Angle Port			
	Sigma 19mm f/2.8 DN Art				36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II	83202 WWL - 1B	Lens FOV 73.5° Converted FOV 127°

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

* Recommended Nauticam underwater optics based on best underwater optical performance

* Recommended Port System