



WET WIDE LENS FOR COMPACT CAMERAS (WWL-C)

130 DEG. FOV WITH COMPATIBLE 24MM LENSES

	CAMERA LENS	GEAR	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE	
N120 CINEMA SYSTEM (RED, CANON, PANASONIC, ZOOM, BLACKMAGIC)	STANDARD ZOOM FULL FRAME	Canon RF 24-50mm f/4.5-6.3 IS STM	16347 RF2450 Gear Set	18709 N120 Flat Port 27 with Bayonet Mount	83203 WWL-C	Lens FOV Converted FOV 84-46.8° 130-72°	
		N120 NIKON Z-MOUNT	Nikkor Z 24-50mm f/4-6.3 Lens	19163 N22450-Z	18767 N120 Macro Port 6	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C
N120 CANON RF-MOUNT	STANDARD ZOOM FULL FRAME	Canon RF 24-50mm f/4.5-6.3 IS STM	19598 CR2450-Z	18709 N120 Flat Port 27 with Bayonet Mount <i>* Unlock the lens before entering the camera into housing</i>	83203 WWL-C	Lens FOV Converted FOV 84-46.8° 130-72°	
		WIDE ANGLE FULL FRAME	Canon RF 24mm f/1.8 Macro IS STM	18707 N120 Macro Port 6	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV 84° 130°
N100 FUJIFILM X-MOUNT	STANDARD ZOOM APSC	Fujifilm XC 15-45mm f/3.5-5.6 OIS PZ	36476 X1545PZ-Z	36478 N100 Flat Port 40	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV Zoom Range 84-35° 130-54° 16-45mm
N100 CANON RF-MOUNT	STANDARD ZOOM APSC	Canon RF-S 18-45mm f/4.5-6.3 IS STM	19596 CRS1845-Z	37181 N100 Flat Port 50	83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV Zoom Range 75-35° 116-52° 18-45mm
N100 NIKON Z-MOUNT	STANDARD ZOOM DX	NIKKOR Z DX 16-50mm f/3.5-6.3 VR	37602 Z1650PZ-Z	37601 N100 Flat Port 29	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV 84-31.5° 130-49°
N100 SONY E-MOUNT	WIDE ANGLE FULL FRAME	Sony FE 24mm f/2.8 G	37130 N100 Flat Port 23	37130 N100 Flat Port 23	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV 84° 130°
		Sigma 24mm f/3.5 DG DN	37127 N100 Flat Port 32	37127 N100 Flat Port 32	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV 84° 130°
N85 MICRO FOUR THIRDS SYSTEM	STANDARD ZOOM FOUR THIRDS	Olympus M.Zuiko Digital ED 12-50mm f/3.5-6.3 EZ	36147 O1250-Z <i>* 36059 O1250-Z for NA-GH5 & NA-EM1X</i>	36161 N85 Macro Port with M77 Thread <i>* 36167 Gear Set for NA-OM1</i>	83251 M77 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV Zoom Range 72-24° 110-37° 14-50mm
		Panasonic LUMIX G VARIO 12-32mm F3.5-5.6 ASPH. ASPH. MEGA O.I.S.	36046 P1232-Z	36165 N85 Power Zoom Macro Port 29	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV 84-37° 130-57°
N85 MICRO FOUR THIRDS SYSTEM	WIDE ANGLE FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 12mm f/2.0	36168 N85 Pancake Port 24	36168 N85 Pancake Port 24	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV 84° 130°
N85 SONY E-MOUNT	STANDARD ZOOM APSC	Sony E PZ 16-50mm f/3.5-5.6 OSS	36172 SE1650-PZ	36228 N85 Macro Port 40 with Knob	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV Zoom Range 80-31° 124-48° 17-50mm
N85 CANON EF-M-MOUNT	STANDARD ZOOM APSC	Canon EF-M 15-45mm f/3.5-6.3 IS STM	36195 CM1545-Z	36135 N85 Macro Port 45	83250 M67 to Bayonet Mount Converter II	83203 WWL-C	Lens FOV Converted FOV Zoom Range 76-33° 117-51° 17-45mm
N50 & COMPACT SYSTEM	SONY	Sony Cyber-shot DSC-RX100 Mark V (17418/17418P NA-RX100V / Pro Package) * 24-70mm (35mm equivalent) <i>* Port is inexchangeable for this housing</i>			83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV 84-34° 130-52°
		Sony Cyber-shot DSC-RX100 Mark VI (17421/17421P NA-RX100VI / Pro Package) * 24-200mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>		38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range 84-46° 130-70° 24-50mm
		Sony Cyber-shot DSC-RX100 Mark VII (17424/17424P NA-RX100VII / Pro Package) * 24-200mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>		38705 N50 Short Port 17 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range 84-46° 130-70° 24-30mm
	CANON	Canon Powershot G5XMKII (17331/17331P NA-G5XII / Pro Package) * 24-120mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>		38763 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range 84-46° 130-71° 24-50mm
		Canon Powershot G7XMKII (17324 NA-G7XII) * 24-100mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>		38763 N50 Short Port 25 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range 84-46° 130-71° 24-50mm
		Canon Powershot G7XMKIII (17330/17330P NA-G7XIII / Pro Package) * 24-100mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>		38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Zoom Range 84-46° 130-71° 24-50mm
	PANASONIC	Panasonic Lumix DC-LX100II (17717 NA-LX100II) * 24-75mm (35mm equivalent) <i>* Port is exchangeable for this housing</i>		38704 N50 Short Port 22 with Bayonet Mount <i>* change port from housing</i>		83203 WWL-C	Lens FOV Converted FOV Working Distance 84-72° 130-112° 24-30mm
		Panasonic Lumix DC-LX10 (LX15) (17714 NA-LX10) * 24-72mm (35mm equivalent) <i>* Port is inexchangeable for this housing</i>			83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL-C	Lens FOV Converted FOV Zoom Range 70-34° 108-53° 32-72mm
	OLYMPUS	Olympus Tough TG5/TG6/TG7 (with MS2 Thread) * 24-100mm (35mm equivalent) <i>* Port is inexchangeable for this housing</i>			83255 MS2 to Bayonet Mount Converter	83203 WWL-C	Lens FOV Converted FOV 84-24° 130-37°
		Olympus Tough TG5/TG6/TG7 (with Bayonet Mount) * 24-100mm (35mm equivalent) <i>* Port is inexchangeable for this housing</i>				83203 WWL-C	Lens FOV Converted FOV 84-24° 130-37°
		Olympus PT-058/ PT-059 Underwater Housing			83256 Bayonet Mount Converter for Olympus PT-058/PT-059	83203 WWL-C	Lens FOV Converted FOV 84-24° 130-37°

83203 WET WIDE LENS FOR COMPACT CAMERAS (WWL-C) 130 deg. FOV with compatible 24mm lenses

Specifications

Dimension (mm)	: DIA156mm x 78mm
Weight in Air	: 1.05kg
Buoyancy in Water	: Negative 0.17 kg
Body Construction	: Hard-anodized aluminum alloy
Lens Construction	: 4 Elements
Lens Coating	: Anti-reflective on both sides Multi-layer Broad-band
Focus Distance	: From front element of lens to infinity
Maximum FOV (underwater)	: 130° (Ref. 24mm equivalent)
Lens Mount	: Bayonet Mount
Depth Rating	: 100m
Pre-installed	: Integrated aluminium float collar

Package includes

- WWL-C with Bayonet Mount
- Front hard lens cap
- Rear lens caps
- Padded carrying bag
- Cleaning cloth
- Lubricant