

N120/N100 0.36X WIDE ANGLE CONVERSION PORT WITH INTEGRATED FLOAT COLLAR & INTERCHANGEABLE PORT MOUNT WACP-1B

FOR FULL FRAME 28MM EQUIVALENT LENSES TO EXTREME SHARP 130°

		CAMERA LENS	GEAR	PORT ADAPTOR	EXTENSION RING	PORT	OPTICAL PERFORMANCE
N120 CINEMA SYSTEM (RED, CANON, PANASONIC, ZOOM, BLACKMAGIC)	STANDARD ZOOM APSC	Canon EF-S 18-55mm f/3.5-5.6 IS STM	16330 RC1855STM Gear Set		22125 N120 Extension Ring 25 II	85206 N120/N100 WACP-1B	On APS-C Sensor Lens FOV 71-29° Converted FOV 123-150° Zoom Range 20-50mm
		Sigma 18-35mm F1.8 DC HSM	16326 RC1835F1.8 Gear Set		22130 + 22135 N120 Extension Ring 30 II + N120 Extension Ring 35 II	85206 N120/N100 WACP-1B	On APS-C Sensor Lens FOV 71-46° Converted FOV 123-178° Zoom Range 20-35mm
	STANDARD ZOOM FULL FRAME	Canon RF 24-50mm f/4.5-6.3 IS STM	16347 RF2450 Gear Set		22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B	Lens FOV 84-46.8° Converted FOV 130-81° Zoom Range 28-50mm
		Canon EF 28-80mm f/3.5-5.6 V Lens	16344 C2880VUSM Gear Set		22130 N120 Extension Ring 30 II	85206 N120/N100 WACP-1B	On APS-C Sensor Lens FOV 51-19° Converted FOV 88-33°
	WIDE ANGLE FULL FRAME	Canon EF 28-70mm f/3.5-4.5 II Lens <i>* This lens is not supported by RSC camera in video mode</i>	16334 RC2870II Gear Set		22125 N120 Extension Ring 25 II	85206 N120/N100 WACP-1B	On Full Frame Sensor Lens FOV 75-30° Converted FOV 130-52°
		Canon RF 16-35mm f/4.5-6.3 IS STM	16345 RF1630 Gear Set		22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B	On APS-C Sensor Lens FOV 75-49° Converted FOV 130-125° Zoom Range 18-30mm
N120 NIKON F-MOUNT	STANDARD ZOOM DX	Nikon AF-S DX Micro NIKKOR 18-55mm f/3.5-5.6G VR II	19144 N1855VRB-Z		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 76-29° Converted FOV 130-50°
		Nikon AF-S Nikkor 28mm f/1.8 G			22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B	Lens FOV 75° Converted FOV 130°
	STANDARD ZOOM FX	Nikon AF Nikkor 28mm f/2.8D				85206 N120/N100 WACP-1B	Lens FOV 75° Converted FOV 130°
		Nikon AF Nikkor 28-70mm f/3.5-4.5D	19148 N2870FS-SD-Z		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 75-34° Converted FOV 130-59°
	WIDE ANGLE FX	Nikon AF-S NIKKOR 16-35mm f/4G ED VR	19138 N1635-Z		22170 N120 Extension Ring 70 II	85206 N120/N100 WACP-1B	On DX Sensor Lens FOV 75-45° Converted FOV 130-178° Zoom Range 18-35mm
		Nikon AF-S 17-35mm f/2.8D IF-ED	19130 N1735-Z		22150 N120 Extension Ring 50 II	85206 N120/N100 WACP-1B	On Full Frame Sensor Lens FOV 75-43° Converted FOV 130-109° Zoom Range 28-35mm
N120 NIKON Z-MOUNT	STANDARD ZOOM FX	Nikkor Z 24-50mm f/4-6.3 Lens	19165 N2450-Z with limiter ring			85206 N120/N100 WACP-1B	Lens FOV 75-47° Converted FOV 130-81° Zoom Range 28-50mm
		Nikkor Z 24-70mm f/4 S Lens	19154 N2470-Z		22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B	Lens FOV 75-70° Converted FOV 130-121° Zoom Range 28-32mm
		Nikkor Z 28-75mm f/2.8 Lens	19162 N2875-Z		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 75-48° Converted FOV 130-83° Zoom Range 28-48mm
SONY E-MOUNT	STANDARD ZOOM APSC	Sony SEL2870 FE 28-70mm f/3.5-5.6 OSS with MegaStep ETZ 21 Adaptor	19158 NE2870-Z		22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B	Lens FOV 75-34° Converted FOV 130-59°
		Canon EF-S 18-55mm f/3.5-5.6 IS STM	19547 C1855STM-Z		22130 N120 Extension Ring 30 II	85206 N120/N100 WACP-1B	Lens FOV 75-27.5° Converted FOV 130-46°
	STANDARD ZOOM FULL FRAME	Sigma 18-35mm F1.8 DC HSM	19552 SC1835F1.8-Z		22130 + 22135 N120 Extension Ring 30 II + N120 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 76.5-44° Converted FOV 132-76°
		Canon EF 28mm f1.8 USM				85206 N120/N100 WACP-1B	Lens FOV 75° Converted FOV 130°
	WIDE ANGLE FULL FRAME	Canon EF 28mm f/2.8 USM				85206 N120/N100 WACP-1B	Lens FOV 75° Converted FOV 130°
		Canon EF 28-70mm f/3.5-4.5 II	19557 C2870FS-SH-Z		22125 N120 Extension Ring 25 II	85206 N120/N100 WACP-1B	Lens FOV 75-34° Converted FOV 130-59°
N120 CANON EF-MOUNT	STANDARD ZOOM APSC	Canon EF 28-80mm f/3.5-5.6 V USM	19559 C2880FS-3V-Z		22130 N120 Extension Ring 30 II	85206 N120/N100 WACP-1B	Lens FOV 75-30° Converted FOV 130-54°
		Canon EF 35mm f/2 IS USM				85206 N120/N100 WACP-1B	Lens FOV 63° Converted FOV 109°
	STANDARD ZOOM FULL FRAME	Canon EF 16-35mm f/2.8 III USM	19554 C1635III-Z		22170 N120 Extension Ring 70 II	85206 N120/N100 WACP-1B	On APS-C Sensor Lens FOV 80-43° Converted FOV 138-74°
		Canon EF 16-35mm f/4 IS USM	19548 C16354-Z		22160 N120 Extension Ring 60 II	85206 N120/N100 WACP-1B	On Full Frame Sensor Lens FOV 75-43° Converted FOV 130-109° Zoom Range 28-35mm
	WIDE ANGLE FULL FRAME	Canon EF 17-40mm f/4L USM	19528 C1740-Z		22140 N120 Extension Ring 40 II	85206 N120/N100 WACP-1B	On APS-C Sensor Lens FOV 77-37° Converted FOV 133-74°
		Canon RF 24-50mm f/4.5-6.3 IS STM	19599 CR2850-Z with limiter ring		22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B	Lens FOV 84-46.8° Converted FOV 130-81° Zoom Range 28-50mm
N120 PANASONIC L-MOUNT	STANDARD ZOOM CANON EF-MOUNT	Panasonic Lumix S 24-105mm f/4	19721 PS24105-Z		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 75-45° Converted FOV 130-112° Zoom Range 28-33mm
		Canon EF 28-70mm f/3.5-5.6 II with Sigma Mount Converter MC-21	19725 CR2870-Z with MC-21		22130 + 22131 N120 Extension Ring 30 II + Focus Knob	85206 N120/N100 WACP-1B	Lens FOV 72-34° Converted FOV 128-59° Zoom Range 30-70mm
	WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 45mm f/2.8 R WR	19557 C2870FS-SH-Z		22125 N120 Extension Ring 25 II	85206 N120/N100 WACP-1B	Lens FOV 75-34° Converted FOV 130-59° Zoom Range 28-70mm
N120 FUJIFILM X-MOUNT	STANDARD ZOOM MEDIUM FORMAT	Fujifilm GF 35-70mm f/4.5-5.6 WR			22140 N120 Extension Ring 40 II	85206 N120/N100 WACP-1B	Lens FOV 76-42.7° Converted FOV 131.5-74° <i>* Minimum focus distance from 2017 to subject is 0.25m at 35mm and 0.10m at 70mm</i>
		Fujifilm GF 45mm f/2.8 R WR			22130 N120 Extension Ring 30 II	85206 N120/N100 WACP-1B	Lens FOV 63° Converted FOV 109°
	CANON EF-MOUNT	Canon EF 28-70mm f/3.5-5.6 II with Metabones EF-GFX mount Smart Expander 1.26x	T80 C2870FS-SH-Z		22150 N120 Extension Ring 50 II	85206 N120/N100 WACP-1B	Lens FOV 75-34° Converted FOV 130-59°
N100 CANON RF-MOUNT	STANDARD ZOOM APSC	Fujifilm XF 18-55mm f/2.8-4 R LM OIS	36474 X1855-Z3		37401 / 37430 N100 Extension Ring 30 / N100 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 75-52° Converted FOV 130-90° Zoom Range 18-30mm
		Canon RF-S 18-45mm f/4.5-6.3 IS STM	19596 CR1845-Z		37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 45 II	85206 N120/N100 WACP-1B	Lens FOV 75-35° Converted FOV 130-60°
N100 SONY E-MOUNT	STANDARD ZOOM FULL FRAME	Sony FE 20-70mm f/4 G	37174 SFE2070-Z	37305 N100 to N120 35.5mm Port Adaptor II	22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B	Lens FOV 75-71° Converted FOV 130-123° Zoom Range 28-30mm
		Sony SEL2870 FE 28-70mm f/3.5-5.6 OSS	37163 SFE2870-Z		37401 / 37430 N100 Extension Ring 30 / N100 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 75° Converted FOV 130°
	STANDARD ZOOM FULL FRAME	Tamron 28-75mm f/2.8 Di III RXD	37159 STE2875-Z	37305 N100 to N120 35.5mm Port Adaptor II	22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B	Lens FOV 75-52° Converted FOV 130-90° Zoom Range 28-45mm
		Sony SEL1635GM2 FE 16-35mm f/2.8 GM II	37175 SFE1635GM2-Z	37305 N100 to N120 35.5mm Port Adaptor II	22140 N120 Extension Ring 40 II	85206 N120/N100 WACP-1B	On APS-C Sensor Lens FOV 75-45° Converted FOV 130-78°
	WIDE ANGLE FULL FRAME	Sony FE PZ 16-35mm f/4 G	37172 SFE1635-Z	37305 N100 to N120 N100 to N120	22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B	On Full Frame Sensor Lens FOV 75-43° Converted FOV 130-109° Zoom Range 28-35mm
		Tamron 20-40mm f/2.8 Di III VXD	37177 STE2040-Z	37305 N100 to N120 35.5mm Port Adaptor II	37403 / 37433 N100 Extension Ring 50 / N100 Extension Ring 55 II	85206 N120/N100 WACP-1B	Lens FOV 75-56.5° Converted FOV 130-98° Zoom Range 28-40mm
N85 MICRO FOUR THIRDS SYSTEM	STANDARD ZOOM FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 12-40mm f/2.8 PRO	36045 O1240-Z	36052 N85 to N120 47mm Port Adaptor with Zoom Knob <i>* SMC1718 onwards for NA-EM1X</i>		85206 N120/N100 WACP-1B	Lens FOV 75-45° Converted FOV 130-68° Zoom Range 14-26mm
		Panasonic LUMIX G X Vario 12-35mm F2.8 / 8 ASPH. POWER O.I.S.	36148 + 36042 O1240-F P1235-F	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SMC1718 onwards for NA-EM1X</i>		85206 N120/N100 WACP-1B	Lens FOV 75-38° Converted FOV 130-57° Zoom Range 14-22mm
	WIDE ANGLE FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 8-25mm f/4 PRO	36071 O825-Z	36401 N85 to N120 55mm Port Adaptor with Lens Control Knob <i>* SMC1718 onwards for NA-EM1X</i>	22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B	Lens FOV 75-47° Converted FOV 130-81° Zoom Range 14-25mm

N120/N100 0.36X Wide Angle Conversion Port with Integrated Float Collar and Interchangeable Port Mount (WACP-1B) For Full Frame 28mm Equivalent Lenses to Extreme Sharp 130°

Specifications		Package Includes	
Dimension (mm)	: DIA 194 x H 174 (from port mount to front lens element)	• WACP-1B with integrated float collar	
Weight in Air	: 3.70 kg	• N120 and N100 Mounting rings	
Buoyancy in Water	: Negative 0.01 kg	• Front hard lens cap	
Body Construction	: Hard-anodized aluminum alloy	• Rear lens caps	
Lens Construction	: 6 Elements in 5 Groups	• Padded carrying bag	
Lens Coating	: Anti-corrosion coating outside of dome	• 90140 N120 Port O-ring	
	: Anti-reflection coating on other surfaces	• 90141 N100 Port O-ring	
Focus Distance	: From front element of lens to infinity	• Cleaning Cloth	
Maximum FOV (underwater)	: 130° (Ref. 28mm equivalent)	• Lubricant	
Lens Mount	: N120/N100 Port Mount		
Depth Rating	: 100m		
Pre-installed	: Integrated aluminium float collar		