



# N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2

## FOR FULL FRAME 14MM EQUIVALENT LENSES TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	PORT ADAPTOR / EXTENSION RING	EXTENSION RING / PORT CONVERTER	PORT	OPTICAL PERFORMANCE
N120 CINEMA SYSTEM EF & RF-MOUNT (RED, CANON, PANASONIC, Z-CAM, BLACKMAGIC)	STANDARD ZOOM FULL FRAME	Canon RF 28-70mm f/2L USM	16343 RC2870Z RC2870Z	22140 N120 Extension Ring 40 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	On Full Frame Sensor Lens FOV 75-63° Converted FOV 85-72° Zoom Range 28-35mm
	WIDE ANGLE APS-C	Canon EF-S 10-18mm f/4.5-5.6 IS STM	16340 RC1018 Gear Set		85204 N120 WACP-2	On APS-C Sensor Lens FOV 108-75° Converted FOV 128-85°
		Canon EF-S 10-22mm f/3.5-4.5 IS USM	16303 + 16304 RC1022-F RC1022-F	21110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	On APS-C Sensor Lens FOV 108-63° Converted FOV 128-72°
		Tokina AT-X 11-20mm f2.8 PRO DX	16328 RTC1120 Gear Set	22120 N120 Extension Ring 20 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	On APS-C Sensor Lens FOV 108-63° Converted FOV 128-72°
	WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	16342 CR1435 Gear Set	21110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	On APS-C Sensor Lens FOV 89-42° Converted FOV 104-48°
		Canon RF 15-35mm f/2.8L IS USM	16341 CR1535 Gear Set	22135 N120 Extension Ring 35 II	85204 N120 WACP-2	On Full Frame Sensor Lens FOV 114-63° Converted FOV 140-72°
		Canon RF 15-30mm f/4.5-6.3 IS STM	16345 CR1530 Gear Set		85204 N120 WACP-2	On APS-C Sensor Lens FOV 84-49° Converted FOV 101-59°
Canon EF 16-35mm f/2.8 II USM		16311 + 16312 RC1635R-Z RC1635R-F	22130 N120 Extension Ring 30 II	85204 N120 WACP-2	On Full Frame Sensor Lens FOV 110-71° Converted FOV 133-81°	
Canon EF 16-35mm f/2.8 III USM		16325 RC1635R Gear Set	22150 N120 Extension Ring 50 II	85204 N120 WACP-2	On APS-C Sensor Lens FOV 84-44° Converted FOV 98-45°	
Canon EF 16-35mm f/2.8 III USM		16325 RC1635R Gear Set	22150 N120 Extension Ring 50 II	85204 N120 WACP-2	On Full Frame Sensor Lens FOV 107-63° Converted FOV 128-72°	
WIDE ANGLE FULL FRAME	Nikkor Z 14-24mm f/2.8 S	TBD Gear Set	21110 N120 Extension Ring 10 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	On Full Frame Sensor Lens FOV 114-72° Converted FOV 140-81°	
	Nikkor Z 14-30mm f/4 S	TBD Gear Set	22110 N120 Extension Ring 10 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	On Full Frame Sensor Lens FOV 114-72° Converted FOV 140-81°	
WIDE ANGLE FX	Nikon AF-S NIKKOR 16-35mm f/4G ED VR	19138 N1635-Z	22150 N120 Extension Ring 50 II	85204 N120 WACP-2	Lens FOV 105-63° Converted FOV 128-72°	
	Nikon AF-S 17-35mm f/2.8D IF-ED	19130 N1735-Z	22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 104-63° Converted FOV 123-72°	
STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S II Lens	19166 (V1) N2470R-Z (V1)	22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 84-34° Converted FOV 98-40°	
WIDE ANGLE FX	Nikkor Z 14-24mm f/2.8 S	19160 (V1) / 19202 (V2) N21424-Z (V1) / Z1424-Z (V2)	21110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 114-87° Converted FOV 140-98°	
	Nikkor Z 14-30mm f/4 S	19156 (V1) / 19203 (V2) N21430-Z (V1) / Z1430-Z (V2)	22110 N120 Extension Ring 10 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	Lens FOV 114-72° Converted FOV 140-81°	
STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S II Lens	19236 (V3) Z2470R-Z (V3)	22155 N120 Extension Ring 55 II	85204 N120 WACP-2	Lens FOV 84-34° Converted FOV 98-40°	
WIDE ANGLE FX	Nikkor Z 14-24mm f/2.8 S	19234 (V3) Z1424-Z (V3)	22135 N120 Extension Ring 35 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 114-87° Converted FOV 140-98°	
	Nikkor Z 14-30mm f/4 S	19235 (V3) Z1430-Z (V3)	22125 N120 Extension Ring 25 II	85204 N120 WACP-2	Lens FOV 114-72° Converted FOV 140-81°	
STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S II Lens	19236 (V3) Z2470R-Z (V3)	22155 N120 Extension Ring 55 II	85204 N120 WACP-2	Lens FOV 84-34° Converted FOV 98-40°	
WIDE ANGLE FX	Nikkor Z 14-24mm f/2.8 S	19202 (V2) / 19234 (V3) Z1424-Z (V2) / Z1424-Z (V3)	22135 N120 Extension Ring 35 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 114-87° Converted FOV 140-98°	
	Nikkor Z 14-30mm f/4 S	19203 (V2) / 19235 (V3) Z1430-Z (V2) / Z1430-Z (V3)	22125 N120 Extension Ring 25 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	Lens FOV 114-72° Converted FOV 140-81°	
WIDE ANGLE APS-C	Canon EF-S 10-18mm f/4.5-5.6 IS STM	19540 C1018-Z		85204 N120 WACP-2	Lens FOV 108-75° Converted FOV 128-85°	
	Canon EF-S 10-22mm f/3.5-4.5 IS STM	19525 C1022-Z	21110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 108-63° Converted FOV 128-72°	
	Tokina AT-X 116 PRO DX AF 11-16mm f2.8	19530 TC1116-Z	21110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 110-81° Converted FOV 133-92°	
	Canon EF 16-35mm f/2.8 II USM	19527 C1635R-Z	22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 107-63° Converted FOV 128-72°	
	Canon EF 16-35mm f/2.8 III USM	19554 C1635R-Z	22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 107-63° Converted FOV 128-72°	
	Canon EF 16-35mm f/4 IS USM	19548 C1635R-Z	22150 N120 Extension Ring 50 II	85204 N120 WACP-2	Lens FOV 108-63° Converted FOV 128-72°	
	Canon RF 28-70mm f/2L USM	19595 RC2870Z	22140 N120 Extension Ring 40 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	Lens FOV 75-63° Converted FOV 85-72° Zoom Range 28-35mm	
WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	19574 CR1435-Z	21110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 114-63° Converted FOV 140-72°	
	Canon RF 15-30mm f/4.5-6.3 IS STM	19597 CR1530-Z		85204 N120 WACP-2	Lens FOV 110-71° Converted FOV 133-81°	
	Canon RF 15-35mm f/2.8L IS USM	19569 CR1535-Z	22135 N120 Extension Ring 35 II	85204 N120 WACP-2	Lens FOV 110-63° Converted FOV 133-72°	
WIDE ANGLE FULL FRAME	Canon RF 14-35mm f/4L IS USM	19632 RF1435-Z	21110 + 22120 N100 to N120 Extension Ring 10 + N120 Extension Ring 20 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 114-63° Converted FOV 140-72°	
	Canon RF 15-35mm f/2.8L IS USM	19631 RF1535-Z	22130 N120 Extension Ring 30 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	Lens FOV 114-63° Converted FOV 140-72°	
WIDE ANGLE FULL FRAME	Panasonic Lumix S PRO 16-35mm f/4	19726 PL1635-Z		85204 N120 WACP-2	Lens FOV 105-63° Converted FOV 128-72°	
	Sigma 14-24mm f2.8 DG DN Art	19726 SLE1424-Z	22125 N120 Extension Ring 25 II	85204 N120 WACP-2	Lens FOV 105-63° Converted FOV 128-72° Zoom Range 20-24mm	
M4/3 MEDIUM FORMAT	Laowa 17mm f/4 GFX Zero-D	19824 + 19825 GL17-A GL17-F	22135 + 22151 N100 to N120 Extension Ring 35 II + Focus Knob	85204 N120 WACP-2	Lens FOV 114° Converted FOV 140°	
WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 20-35mm F4 R WR	19827 GF2035-Z	22135 N120 Extension Ring 35 II	85204 N120 WACP-2	Lens FOV 108-76° Converted FOV 132-83°	
	Fujifilm GF 23mm F4 R LM WR		22120 N120 Extension Ring 20 II	85204 N120 WACP-2	Lens FOV 100° Converted FOV 118°	
CANON EF-MOUNT	Canon EF 16-35mm f/2.8 III USM with Metabones EF-CX mount Smart Expander 1.26x	TBD CGF1635R-Z	22180 N120 Extension Ring 80 II	85204 N120 WACP-2	Lens FOV 107-63° Converted FOV 128-72°	
	Canon EF 16-35mm f/4 IS USM with Metabones EF-CX mount Smart Expander 1.26x	TBD CGF1635R-Z	22160 N120 Extension Ring 60 II	85204 N120 WACP-2	Lens FOV 107-63° Converted FOV 128-72°	
STANDARD ZOOM FULL FRAME	Sony FE 20-70mm f/4 G	37174 SFE2070-Z	37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2 * slight vignetting at 20mm in RAW format	Lens FOV 94-55° Converted FOV 116-73° Zoom Range 20-38mm	
	Sony SEL2470GM FE 24-70mm f/2.8 GM	37151 SFE2470GM-Z	37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 84-34° Converted FOV 98-72° Zoom Range 24-35mm	
	Sigma 24-70mm f/2.8 DG DN Art	37171 SFP2470-Z	37305 N100 to N120 35.5mm Port Adaptor II	22120 N120 Extension Ring 20 II	85204 N120 WACP-2	Lens FOV 84-64° Converted FOV 98-74° Zoom Range 24-34mm
	Sony FE 14mm f/1.8 GM		37306 N100 to N120 25mm Port Adaptor	85204 N120 WACP-2	Lens FOV 114° Converted FOV 140°	
	Sony SEL1635GM FE 16-35mm f/2.8 GM	37155 SFE1635GM-Z	37305 N100 to N120 35.5mm Port Adaptor II	22130 N120 Extension Ring 30 II	85204 N120 WACP-2	Lens FOV 107-63° Converted FOV 128-72°
	Sony SEL1635GM-F FE 16-35mm f/2.8 GM II	37175 + 37156 SFE1635GM-Z + SFE1635GM-F	37305 N100 to N120 35.5mm Port Adaptor II	22110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 107-63° Converted FOV 128-72°
	Sony SEL1635GM-F FE 16-35mm f/2.8 GM II	37175 + 37176 SFE1635GM-Z + SFE1635GM-F	37305 N100 to N120 35.5mm Port Adaptor II	22110 N120 Extension Ring 10 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	Lens FOV 107-63° Converted FOV 128-72°
	Sony SEL1635Z Vario-Tessar T* FE 16-35mm f/4 ZA OSS	37145 + 37146 SEL1635-Z + SEL1635-F	37305 N100 to N120 35.5mm Port Adaptor II	21110 N120 Extension Ring 10	85204 N120 WACP-2 * This setup is only compatible with WACP-2 before SN:AS26311	Lens FOV 107-63° Converted FOV 128-72°
	Sony FE PZ 16-35mm f/4 G	37172 SFE1635-Z	37306 N100 to N120 25mm Port Adaptor	22110 N120 Extension Ring 10 II	85204 N120 WACP-2 * This setup is only compatible with WACP-2 SN:AS26311 onwards	Lens FOV 107-63° Converted FOV 128-72°
	Sony FE 24mm f/1.4 GM		37305 N100 to N120 35.5mm Port Adaptor II	85204 N120 WACP-2	Lens FOV 84° Converted FOV 98°	
Sigma 14-24mm f2.8 DG DN	19726 SLE1424-Z	37305 N100 to N120 35.5mm Port Adaptor II	22125 N120 Extension Ring 25 II	85204 N120 WACP-2	Lens FOV 94-84° Converted FOV 115-98° Zoom Range 20-24mm	

### 85204 N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 (WACP-2) For Full Frame 14mm Equivalent Lenses to 140° Full Zoom-through

#### Specifications

Dimension (mm)	:	DIA 297 x H 220 (from port mount to front lens element)
Weight in Air	:	7.35 kg
Buoyancy in Water	:	Negative 0.27 kg
Body Construction	:	Hard-anodized aluminum alloy
Lens Construction	:	4 Elements
Lens Coating	:	Anti-corrosion coating outside of dome Anti-reflection coating on other surfaces
Focus Distance	:	From front element of lens to infinity
Maximum FOV (underwater)	:	140° (Ref. 28mm equivalent)
Lens Mount	:	N120 Port Mount
Depth Rating	:	100m
Pre-installed	:	Integrated aluminium float collar

#### Package includes

- WACP-2
- Front hard lens cap
- Rear lens caps
- Padded carrying bag
- 90140 N120 Port O-ring
- Cleaning Cloth
- Lubricant

Last Updated : 2026-03-27

\* This port chart is subject to updating as new information becomes available