

N120/N100 0.36X WIDE ANGLE CONVERSION PORT WITH INTEGRATED FLOAT COLLAR & INTERCHANGEABLE PORT MOUNT WACP-1B

FOR FULL FRAME 28MM EQUIVALENT LENSES TO EXTREME SHARP 130°

		CAMERA LENS	GEAR	PORT ADAPTOR / EXTENSION RING	EXTENSION RING / PORT CONVERTER	PORT	OPTICAL PERFORMANCE			
N120 CANON EF-MOUNT	STANDARD ZOOM FULL FRAME	Canon RF 24-50mm F4.5-6.3 IS STM	16347 CR2450 Gear Set		22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	84-46.8° 130-81° 28-50mm	
		Canon RF 28-80mm F3.5-5.6 V Lens	16344 CR2880VSM Gear Set		22130 N120 Extension Ring 30 II	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	51-19° 130-81° 28-80mm	
		Canon RF 15-30mm F4.5-6.3 IS STM	16345 CR1530 Gear Set		22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	75-49° 130-85° 18-30mm	
	WIDE ANGLE FULL FRAME	Canon EF 16-35mm F2.8 III USM	16325 CR1635III Gear Set		22170 N120 Extension Ring 70 II	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	71-45° 123-78° 20-35mm	
		Canon EF 24-50mm F4.5-6.3 IS STM	16347 CR2450 Gear Set		22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B		On Full Frame Sensor Lens FOV Converted FOV Zoom Range	75-47° 130-81° 28-50mm	
		Canon EF 28-80mm F3.5-5.6 V Lens	16344 CR2880VSM Gear Set		22130 N120 Extension Ring 30 II	85206 N120/N100 WACP-1B		On Full Frame Sensor Lens FOV Converted FOV Zoom Range	51-19° 130-81° 28-80mm	
	N120 NIKON Z-MOUNT	STANDARD ZOOM FX	Nikon AF-S NIKKOR 18-55mm F3.5-5.6 VR with Nikon FTZ1 mount adaptor	19230 Chain gear set		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75-31° 130-54°
			Nikon Z 24-50mm F4.5-6.3 Lens	TBD Gear Set		22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B		On Full Frame Sensor Lens FOV Converted FOV Zoom Range	75-47° 130-81° 28-50mm
			Nikon Z 35mm F1.8 S			22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On Full Frame Sensor Lens FOV Converted FOV	63° 110°
		WIDE ANGLE FX	Nikon AF-S NIKKOR 28mm F2.8D			22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75° 130°
Nikon AF NIKKOR 28mm F2.8D					22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75° 130°	
Nikon AF NIKKOR 28-70mm F3.5-4.5D			19148 N2870FS 50-Z		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75-34° 130-59°	
N120 SONY E-MOUNT		STANDARD ZOOM FULL FRAME	Sony SEL2870 FE 28-70mm F3.5-5.6 OSS with Megadap ETZ 21 Adaptor	TBD Gear Set		22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV	75-34° 130-59°
			Nikon AF-S NIKKOR 18-55mm F3.5-5.6 VR with Nikon FTZ1 mount adaptor	19230 Chain gear set		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75-31° 130-54°
			Nikon Z 24-50mm F4.5-6.3 Lens	TBD Gear Set		22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B		On Full Frame Sensor Lens FOV Converted FOV Zoom Range	75-47° 130-81° 28-50mm
		WIDE ANGLE FULL FRAME	Nikon AF-S NIKKOR 28mm F1.8 S			22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75° 130°
	Nikon AF NIKKOR 28mm F2.8D				22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75° 130°	
	Nikon AF NIKKOR 28-70mm F3.5-4.5D		19148 N2870FS 50-Z		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75-34° 130-59°	
	N120 FUJIFILM X-MOUNT	STANDARD ZOOM FULL FRAME	Nikon AF-S NIKKOR 18-55mm F3.5-5.6 VR with Nikon FTZ1 mount adaptor	19230 Chain gear set		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75-31° 130-54°
			Nikon Z 24-50mm F4.5-6.3 Lens	TBD Gear Set		22110 N120 Extension Ring 10 II	85206 N120/N100 WACP-1B		On Full Frame Sensor Lens FOV Converted FOV Zoom Range	75-47° 130-81° 28-50mm
			Nikon Z 35mm F1.8 S			22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On Full Frame Sensor Lens FOV Converted FOV	63° 110°
		WIDE ANGLE FULL FRAME	Nikon AF-S NIKKOR 28mm F1.8 S			22120 N120 Extension Ring 20 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75° 130°
Nikon AF NIKKOR 28mm F2.8D					22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75° 130°	
Nikon AF NIKKOR 28-70mm F3.5-4.5D			19148 N2870FS 50-Z		22135 N120 Extension Ring 35 II	85206 N120/N100 WACP-1B		On DX Sensor Lens FOV Converted FOV	75-34° 130-59°	
N120 OLYMPUS M.ZUIKO DIGITAL		STANDARD ZOOM FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 12-40mm F2.8 PRO	36045 O1240-Z		36052 N85 to N120 47mm Port Adaptor with Zoom Knob	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	75-45° 130-48° 14-26mm
			Olympus M.ZUIKO DIGITAL ED 8-25mm F4 PRO	36071 O825-Z		36401 N85 to N120 47mm Port Adaptor with Zoom Knob	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	75-38° 130-42° 14-22mm
			Panasonic LUMIX G X Vario 12-35mm F2.8 II ASPH. POWER O.I.S.	36148 + 36042 P1235-F		36052 N85 to N120 47mm Port Adaptor with Zoom Knob	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	75-40° 130-49° 14-30mm
		WIDE ANGLE FOUR THIRDS	Olympus M.ZUIKO DIGITAL ED 8-25mm F4 PRO	36071 O825-Z		36401 N85 to N120 47mm Port Adaptor with Zoom Knob	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	75-47° 130-41° 14-25mm
	Olympus M.ZUIKO DIGITAL ED 12-40mm F2.8 PRO		36045 O1240-Z		36052 N85 to N120 47mm Port Adaptor with Zoom Knob	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	75-45° 130-48° 14-26mm	
	Panasonic LUMIX G X Vario 12-35mm F2.8 II ASPH. POWER O.I.S.		36148 + 36042 P1235-F		36052 N85 to N120 47mm Port Adaptor with Zoom Knob	85206 N120/N100 WACP-1B		On APS-C Sensor Lens FOV Converted FOV Zoom Range	75-40° 130-49° 14-30mm	

85206
N120/N100 0.36X Wide Angle Conversion Port with Integrated Float Collar and Interchangeable Port Mount (WACP-1B)
For Full Frame 28mm Equivalent Lenses to extreme sharp 130°

<p>Specifications</p> <ul style="list-style-type: none"> Dimension (mm) : DIA 194 x H 174 (from port mount to front lens element) Weight in Air : 3.70 kg Buoyancy in Water : Negative 0.01 kg Body Construction : Hard-anodized aluminium alloy Lens Construction : 6 Elements in 5 Groups Lens Coating : Anti-reflection coating outside of dome Focus Distance : Anti-reflection coating on other surfaces Maximum FOV : From front element of lens to infinity (underwater) : 130° (Ref. 28mm equivalent) Lens Mount : N120/N100 Port Mount Depth Rating : 100m Pre-installed : Integrated aluminium float collar 	<p>Package includes</p> <ul style="list-style-type: none"> • WACP-1B with integrated float collar • N120 and N100 Mounting rings • Front hard lens cap • Rear lens caps • Padded carrying bag • 90140 N120 Port O-ring • 90141 N100 Port O-ring • Cleaning Cloth • Lubricant
--	--