



N85 PORT SYSTEM FOR CANON EF-M-MOUNT CAMERA SYSTEM (APS-C Format Lens)

| | CAMERA LENS | GEAR | PORT ADAPTOR | PORT | MOUNT CONVERTER | WET LENS | OPTICAL PERFORMANCE |
|------------------------|---|-------------------|--|------------------------------------|--|--|--|
| STANDARD ZOOM APS-C | Canon EF-M 15-45mm f/3.5-6.3 IS STM | 36195 CM1545-Z | | 36135 N85 Macro Port 45 | SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(Included in all SMC/CMC packaging)</i> | 81301 CMC - 1 | Max. Magnification 0.8X Working Distance 37-81mm |
| | | | | | SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC | 81302 CMC - 2 | Max. Magnification 0.7X Working Distance 59-150mm |
| | | | | | 83250 M67 to Bayonet Mount Converter II | * 83202 WWL - 1B | Lens FOV 74-33° Converted FOV 128-57° Zoom Range 18-45mm |
| | | | | | | 83203 WWL - C | Lens FOV 76-33° Converted FOV 117-51° Zoom Range 17-45mm |
| | Canon EF-M 22mm f/2 STM | | | 36126 E16 Mancake Port | 83250 M67 to Bayonet Mount Converter II | 83202 WWL - 1B | Lens FOV 63° Converted FOV 109° |
| CANON EF-MOUNT | Canon EF 8-15mm f/4L Fisheye USM with Canon EF-M Lens Adapter Kit | 19537 C815-Z | 36184 N85 to N120 41.5mm Port Adaptor <i>* This setup is only compatible with with 36184 SN:A367377 onwards, older version 36184 can be upgraded using lock mechanism 95851</i> | 22130 N120 Extension Ring 30 II | * 18811 140mm Optical Glass Fisheye Port with Removable Shade | | |
| | Canon EF 100mm f/2.8L Macro IS USM with Canon EF-M Lens Adapter Kit | | 36204 N85 to N120 60mm Port Adaptor <i>* This setup is only compatible with with 36204 SN:A457812 onwards, older version 36204 can be upgraded using lock mechanism 95851</i> | 22130 N120 Extension Ring 30 II | 18704 Macro Port 41 | SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(Included in all SMC/CMC packaging)</i> | 81202 SMC - 2 Max. Magnification 3.4X Working Distance 23-39mm |
| | | 19523 C100IS-F | 36184 N85 to N120 41.5mm Port Adaptor <i>* This setup is only compatible with with 36184 SN:A367377 onwards, older version 36184 can be upgraded using lock mechanism 95851</i> | | 18703 Macro Port 94 | SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC | 81302 CMC - 2 Max. Magnification 2.1X Working Distance 53-127mm |
| | Other Canon EF-mount Lenses with Canon EF-M Lens Adapter Kit | | 36184 N85 to N120 41.5mm Port Adaptor <i>* This setup is only compatible with with 36184 SN:A367377 onwards, older version 36184 can be upgraded using lock mechanism 95851</i> | | N120 Canon EF-Mount Port System | | |

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APS-C - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System

Last Updated : 2026-03-27

* This port chart is subject to updating as new information becomes available