



N100 PORT SYSTEM FOR Canon RF-S CAMERA SYSTEM (RF-S & EF-Mount Format Lens)

	CAMERA LENS	GEAR	PORT BASE / PORT ADAPTOR	EXTENSION RING	PORT	MOUNT CONVERTER	WET LENS	OPTICAL PERFORMANCE
MACRO APSC	Canon RF 100mm f/2.8L Macro IS USM	19575 CRF100-F	37305 N100 to N120 35.5mm Port Adaptor II	37430 N100 Extension Ring 30 II	37126 N100 Macro Port 105	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81202 SMC - 2	Max. Magnification 3.3X Working Distance 16-35mm
					18703 Macro Port 94		81203 SMC - 3	Max. Magnification 2.3X Working Distance 30-100mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81501 MFO-1	Max. Magnification 1.6X Working Distance 56-1072mm
								81503 MFO-3
	Canon RF-S 18-45mm f4.5-6.3 IS STM	19596 CR1845-Z			37181 N100 Flat Port 50	SMC/CMC Option 1 - M67 Thread 81228 M67 Spacer Ring for SMC/CMC <i>(included in all SMC/CMC packaging)</i>	81301 CMC - 1	Max. Magnification 0.8X Working Distance 44-81mm
							81302 CMC - 2	Max. Magnification 0.6X Working Distance 68-140mm
						SMC/CMC Option 2 - Bayonet Mount 83250 + 83214 M67 to Bayonet Mount Converter II + Bayonet Mount Adaptor for SMC/CMC	81501 MFO-1	Max. Magnification 0.28X Working Distance 167-1110mm
								* 83202 WWL - 1B
						83250 M67 to Bayonet Mount Converter II <i>(included in all MWL-1 packaging)</i>	83203 WWL - C	Lens FOV 75-35° Converted FOV 116-52° Zoom Range 18-45mm
								86201 MWL - 1
STANDARD ZOOM APSC				37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	* 85206 N120/N100 WACP - 1B			Lens FOV 75-35° Converted FOV 130-60°
					85203 N100 WACP-1			
					85205 N100 WACP - C			
			37305 N100 to N120 35.5mm Port Adaptor II <i>* This setup is only compatible with 37305 SN:A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851</i>		85206 N120/N100 WACP - 1B			
				37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	85207 N120/N100 FCP-1			Lens FOV 74-34° Converted FOV 170-62°
WIDE ANGLE APSC	Canon RF-S 10-18mm f/4.5-6.3 IS STM	19596 CR1845-Z		37402 / 37432 N100 Extension Ring 40 / N100 Extension Ring 40 II	37129 N100 180mm Optical Glass Wideangle Dome Port			
					18802 8.5" Acrylic dome port			
					18809 180mm Optical Glass Wide Angle Port			
					18812 230mm Optical Glass Wide Angle Port II			
CANON EF-MOUNT	Canon EF-mount Lenses with Canon Mount Adaptor EF-EOS R		37305 N100 to N120 35.5mm Port Adaptor II <i>* This setup is only compatible with 37305 SN:A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851</i>		N120 Canon EF-Mount Port System			
	Canon RF mount Fullframe Lenses		37305 N100 to N120 35.5mm Port Adaptor II <i>* This setup is only compatible with 37305 SN:A544975 onwards, older version 37305 can be upgraded using lock mechanism 95851</i>		N120 Canon RF-Mount Port System			

Max. Magnification is the maximum ratio that a subject can be reproduced on a camera's image sensor (APSC - 22.3 x 15mm, Full Frame - 36 x 24mm) at the closest working distance.

Working distance operates from the distance between the subject and the front element of the close-up lens.

- * Recommended Nauticam underwater optics based on best underwater optical performance
- * Recommended Port System