N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2
FOR FULL FRAME 14MM EQUIVALENT LENSES TO 140° FULL ZOOM-THROUGH

	CAMERA LENS	GEAR	MODULE PORT EXTENSION RING	PORT CONVERTER	PORT	OPTICAL PERFORMANCE
STANDARD ZOOM FULL FRAME	Canon RF 28-70mm OL USM	16343 RC28190 RC28193		21140 / 22140 N120 Extension Ring 40 II / III	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards.	On Full Frame Sensor Lens FOV: 114-68° Converted FOV: 65-72° Zoom Range: 28-35mm
WIDE ANGLE APS-C	Canon EF-S 10-18mm f/4.5-5.6 IS STM	16340 RC1618 Gear Set		21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	On APS-C Sensor Lens FOV: 128-70° Converted FOV: 128-90°
	Canon EF-S 10-22mm f/3.5-4.5 IS USM	16303 + 16304 RC1022-1 RC1022-F		22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	On APS-C Sensor Lens FOV: 108-65° Converted FOV: 128-72°
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	On APS-C Sensor Lens FOV: 108-65° Converted FOV: 128-72°
	Tokina AT-X 11-20mm f/2.8 PRO DX	16328 RTC1120 Gear Set		21120 / 22120 N120 Extension Ring 20 II / III	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	On APS-C Sensor Lens FOV: 98-65° Converted FOV: 118-79°
N120 CINEMA SYSTEM LIE & BF-MOUNT (REFS: CANON, PANASONIC, SONY, MEVO, BLACKMAGIC)	Canon RF 14-35mm f/4L IS USM	16342 CR1435 Gear Set		21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	On APS-C Sensor Lens FOV: 89-42° Converted FOV: 104-49° On Full Frame Sensor Lens FOV: 114-53° Converted FOV: 140-72°
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	On APS-C Sensor Lens FOV: 89-42° Converted FOV: 104-49° On Full Frame Sensor Lens FOV: 114-53° Converted FOV: 140-72°
WIDE ANGLE FULL FRAME	Canon RF 15-35mm f/2.8L IS USM	16341 CR1535 Gear Set		21120 / 22120 N120 Extension Ring 20 II / III	85204 N120 WACP - 2	On APS-C Sensor Lens FOV: 84-42° Converted FOV: 98-48° On Full Frame Sensor Lens FOV: 110-53° Converted FOV: 133-72°
	Canon RF 15-35mm f/4-5.6 IS STM	16345 CR1535 Gear Set		21120 / 22120 N120 Extension Ring 20 II / III	85204 N120 WACP - 2	On APS-C Sensor Lens FOV: 84-48° Converted FOV: 101-58° On Full Frame Sensor Lens FOV: 110-71° Converted FOV: 133-91°
	Canon EF 16-35mm f/2.8 USM	16311 + 16312 RC16200-2 + RC16205-F		21130 / 22130 N120 Extension Ring 30 II / III	85204 N120 WACP - 2	On APS-C Sensor Lens FOV: 84-44° Converted FOV: 98-51° On Full Frame Sensor Lens FOV: 107-63° Converted FOV: 128-72°
	Canon EF 16-35mm f/2.8 III USM	16325 RC16300 Gear Set		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	On APS-C Sensor Lens FOV: 84-44° Converted FOV: 98-51° On Full Frame Sensor Lens FOV: 107-63° Converted FOV: 128-72°
STANDARD ZOOM FULL FRAME	Nikkor Z 14-24mm f/2.8 S	98529 Cinema gear set		22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	On Full Frame Sensor Lens FOV: 114-83° Converted FOV: 140-98°
WIDE ANGLE FULL FRAME	Nikkor Z 14-30mm f/4 S	TBD Gear Set			85204 N120 WACP - 2	On Full Frame Sensor Lens FOV: 114-73° Converted FOV: 140-91°
N120 NIKON F-MOUNT ZOOM	Nikon AF-S NIKKOR 16-35mm f/4G ED VR	19138 N1635-Z		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	Lens FOV: 105-63° Converted FOV: 128-72°
	Nikon AF-S 17-35mm f/2.8D IF-ED	19130 N1735-Z		21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 104-63° Converted FOV: 123-72°
STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S Lens	19198 N2470-Z		21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 84- 34° Converted FOV: 98-40°
N120 NIKON Z-MOUNT WIDE ZOOM (FX)	Nikkor Z 14-24mm f/2.8 S	19160 N2124-Z		21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 114-81° Converted FOV: 140-98°
WIDE ANGLE FX				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
	Nikkor Z 14-30mm f/4 S	19158 N2140-Z			85204 N120 WACP - 2	Lens FOV: 114-73° Converted FOV: 140-91°
STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S Lens	19236 Z24T05-Z9		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	Lens FOV: 84- 34° Converted FOV: 98-40°
N120 NIKON Z-MOUNT WIDE ZOOM (FX)	19236 + 19246 Z24T05-Z9 + Z24T05-F9	22225 N120 FTZ Adapter Eff. 25 with Knob		21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	
WIDE ANGLE FX	Nikkor Z 14-24mm f/2.8 S	19234 Z1424-Z9		21135 / 22135 N120 Extension Ring 35 I / II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 114-81° Converted FOV: 140-98°
					85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
	Nikkor Z 14-30mm f/4 S	19235 Z1430-Z9	22225 N120 FTZ Adapter Eff. 25 with Knob	22125 N120 Extension Ring 25 II	85204 N120 WACP - 2	Lens FOV: 114-73° Converted FOV: 140-91°
STANDARD ZOOM FX	Nikkor Z 24-70mm f/2.8 S Lens	19236 Z24T05-Z9		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	Lens FOV: 84- 34° Converted FOV: 98-40°
N120 NIKON Z-MOUNT WIDE ZOOM (FX)	Nikkor Z 14-24mm f/2.8 S	19234 Z1424-Z9		21135 / 22135 N120 Extension Ring 35 I / II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 114-81° Converted FOV: 140-98°
WIDE ANGLE FX					85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
	Nikkor Z 14-30mm f/4 S	19235 Z1430-Z9	22225 N120 FTZ Adapter Eff. 25 with Knob	22125 N120 Extension Ring 25 II	85204 N120 WACP - 2	Lens FOV: 114-73° Converted FOV: 140-91°
WIDE ANGLE APS-C	Canon EF-S 10-18mm f/4.5-5.6 IS STM	19049 C1018-Z		21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 108-70° Converted FOV: 128-89°
N120 CANON EF-MOUNT	Canon EF-S 10-22mm f/3.5-4.5 IS STM	19025 C1022-Z		22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
				21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 108-65° Converted FOV: 128-72°
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
	Tokina AT-X 116 PRO DX AF 11-16mm f/2.8	19030 TC1116-Z		21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 110-81° Converted FOV: 133-92°
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/2.8 USM	19527 C16350-Z		21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 107-63° Converted FOV: 128-72°
	Canon EF 16-35mm f/2.8 III USM	19554 C16350-Z		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	Lens FOV: 107-63° Converted FOV: 128-72°
	Canon EF 16-35mm f/4 IS USM	19548 C16354-Z		21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 108-63° Converted FOV: 128-72°
STANDARD ZOOM FULL FRAME	Canon RF 28-70mm OL USM	19555 CR2870-Z		21140 / 22140 N120 Extension Ring 40 I / II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	Lens FOV: 75-63° Converted FOV: 85-72° Zoom Range: 28-35mm
N120 CANON RF-MOUNT WIDE ZOOM	Canon RF 14-35mm f/4L IS USM	19574 CR1435-Z		21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 114-83° Converted FOV: 140-72°
WIDE ANGLE FULL FRAME				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
	Canon RF 15-30mm f/4.5-6.3 IS STM	19597 CR1530-Z			85204 N120 WACP - 2	Lens FOV: 110-71° Converted FOV: 133-91°
	Canon RF 15-35mm f/2.8L IS USM	19569 CR1535-Z		21120 / 22120 N120 Extension Ring 20 II / III	85204 N120 WACP - 2	Lens FOV: 110-53° Converted FOV: 133-72°
N120 CANON RF-MOUNT WIDE ZOOM WIDE ANGLE FULL FRAME	Canon RF 14mm f/1.4 L VCM			21125 / 22125 N120 Extension Ring 25 I / II	85204 N120 WACP - 2	Lens FOV: 114° Converted FOV: 140°
	Canon RF 14-35mm f/4L IS USM	19632 + 19646 RF1435-Z + RF1435-F * Will not be compatible with R6III housing		21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 114-83° Converted FOV: 140-72°
	Canon RF 15-35mm f/2.8L IS USM	19631 + 19643 RF1535-Z + RF1535-F * Will not be compatible with R6III housing		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	Lens FOV: 110-63° Converted FOV: 133-72°
N120 PANASONIC L-MOUNT WIDE ANGLE FULL FRAME	Panasonic Lumix S PRO 16-35mm f/4	19728 PL1635-Z			85204 N120 WACP - 2	Lens FOV: 105-63° Converted FOV: 128-72°
	Sigma 14-24mm f/2.8 DG DN Art	19738 SL5142A-Z		21125 / 22125 N120 Extension Ring 25 I / II	85204 N120 WACP - 2	Lens FOV: 105-63° Converted FOV: 128-72° Zoom Range: 20-24mm
N120 HASSELBLAD H-MOUNT WIDE ANGLE MEDIUM FORMAT	Leica 17mm f/4 GR Zeiss D	19824 + 19825 OL17 A + OL17 F		21135 + 22151 / 22135 + 22151 N120 Extension Ring 35 I + Focus Knob / N120 Extension Ring 35 II + Focus Knob	85204 N120 WACP - 2	Lens FOV: 114° Converted FOV: 140°
N120 FUJIFILM G-MOUNT WIDE ANGLE MEDIUM FORMAT	Fujifilm GF 30-35mm F4 R WR	19827 GF3035-Z		21135 / 22135 N120 Extension Ring 35 I / II	85204 N120 WACP - 2	Lens FOV: 108-76° Converted FOV: 132-93°
	Fujifilm GF 23mm F4 R LM WR			21120 / 22120 N120 Extension Ring 20 I / II	85204 N120 WACP - 2	Lens FOV: 100° Converted FOV: 119°
CANON EF-MOUNT WIDE ANGLE FULL FRAME	Canon EF 16-35mm f/2.8 USM with Metabones EF-GFX mount Smart Extender 1.25x	TBD CGF16350-Z		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	Lens FOV: 107-63° Converted FOV: 128-72°
	Canon EF 16-35mm f/4 IS USM with Metabones EF-GFX mount Smart Extender 1.25x	TBD CGF16354-Z		21150 / 22150 N120 Extension Ring 60 I / II	85204 N120 WACP - 2	Lens FOV: 107-63° Converted FOV: 128-72°
N120 HASSELBLAD H-MOUNT WIDE ANGLE MEDIUM FORMAT	Hasselblad XCD 20-35mm f/3.2-4.5 E	19863 XC0035-Z		21120 / 22120 N120 Extension Ring 20 I / II	85204 N120 WACP - 2	Lens FOV: 110-76° Converted FOV: 140-98°
STANDARD ZOOM FULL FRAME	Sony FE 20-70mm f/4 G	37174 SF2070-Z	37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851	21125 / 22125 N120 Extension Ring 25 I / II	85204 N120 WACP - 2 * slight vignetting at 20mm in RAW format	Lens FOV: 94-59° Converted FOV: 110-72° Zoom Range: 20-38mm
	Sony SEL24105G FE 24-105mm f/2.8 GM	37151 SF24T05M-Z	37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 84-34° Converted FOV: 98-72° Zoom Range: 24-35mm
		37151 + 37152 SF24T05M-Z + SF24T05M-F				
	Sigma 24-70mm f/2.8 DG DN Art	37171 SGF24T0-Z	37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851	21120 / 22120 N120 Extension Ring 20 I / II	85204 N120 WACP - 2	Lens FOV: 84-84° Converted FOV: 98-72° Zoom Range: 24-34mm
N100 SONY E-MOUNT WIDE ANGLE FULL FRAME	Sony FE 14mm f/1.8 GM		37306 N100 to N120 25mm Port Adapter	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 114° Converted FOV: 140°
	Sony SEL1635GM FE 16-35mm F2.8 GM	37165 SFE1635GM-Z	37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851	21130 / 22130 N120 Extension Ring 30 I / II	85204 N120 WACP - 2	Lens FOV: 107-63° Converted FOV: 128-77°
		37165 + 37166 SFE1635GM-Z + SFE1635GM-F				
	Sony SEL1635GM2 FE 16-35mm f/2.8 GM II	37175 SFE1635GM2-Z	37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851	21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 107-63° Converted FOV: 128-77°
		37175 + 37176 SFE1635GM2-Z + SFE1635GM2-F		22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
WIDE ANGLE FULL FRAME	Sony SEL1635Z Vario-Tessar T* FE 16-35mm F4 ZA OSS	37146 + 37146 SE1635Z-Z + SE1635-F	37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851	21110 N120 Extension Ring 10	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 before SN:A526311	Lens FOV: 107-63° Converted FOV: 128-77°
				22110 N120 Extension Ring 10 II	85204 N120 WACP - 2 * This setup is only compatible with WACP-2 SN:A526311 onwards	
	Sony FE PZ 16-35mm f/4 G	37172 SFE1635-Z	37306 N100 to N120 25mm Port Adapter		85204 N120 WACP - 2	Lens FOV: 107-63° Converted FOV: 128-77°
	Sony FE 24mm f/1.4 GM		37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851		85204 N120 WACP - 2	Lens FOV: 84° Converted FOV: 98°
	Sigma 14-24mm F2.8 DG DN	19738 SL5142A-Z	37305 N100 to N120 35.5mm Port Adapter II * This setup is only compatible with 37305 SN:A04475 onwards, older version 37305 can be upgraded using lock mechanism 95851	21125 / 22125 N120 Extension Ring 25 I / II	85204 N120 WACP - 2	Lens FOV: 94-84° Converted FOV: 110-98° Zoom Range: 20-24mm

85204
N120 0.57X WIDE ANGLE CONVERSION PORT 2 WACP-2 (WACP-2)
For Full Frame 14mm Equivalent Lenses to 140° Full Zoom-through

Specifications

Dimension (mm)	:	DIA 297 x H 220 (from port mount to front lens element)
Weight in Air	:	7.35 kg
Buoyancy in Water	:	Negative 0.27 kg
Body Construction	:	Hard-anodized aluminum alloy
Lens Construction	:	4 Elements
Lens Coating	:	Anti-corrosion coating outside of dome Anti-reflection coating on other surfaces
Focus Distance	:	0.3m to infinity (front of lens to infinity
Lens Angle	:	140° (Ref. 28mm equivalent)
(underwater)		
Lens Mount	:	N120 Port Mount
Depth Rating	:	100m
Pre-installed	:	Integrated aluminum float collar

Package includes

- WACP-2
- Front hard lens cap
- Rear lens caps
- Padded carrying bag
- 90140 N120 Port O-ring
- Cleaning Cloth
- Lubricant

Last Updated : 2026-07-27
* This port chart is subject to updating as new information becomes available